

LEU fuels for medium and high power research reactors in Europe project LEU-FOREvER

S. Valance, H. Breitkreutz, Y. Calzavara, M. Hrehor, F. Huet, J. Jaroszewicz,

H. Palancher, B. Stepnik, S. van den Berghe

▶ To cite this version:

S. Valance, H. Breitkreutz, Y. Calzavara, M. Hrehor, F. Huet, et al.. LEU fuels for medium and high power research reactors in Europe project LEU-FOREvER. International Topical Meeting on Research Reactor Fuel Management, Mar 2018, Munich, Germany. cea-02339120

HAL Id: cea-02339120 https://cea.hal.science/cea-02339120

Submitted on 13 Dec 2019

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.





This project has received funding from the Euratom research and training programme 2014-2018 under grant agreement No 754378

LEU fuels for medium and high power research reactors in Europe: project LEU-FOREvER

CEA | CVR | Framatome | ILL | LGI | NCBJ SCK-CEN | TechnicAtome | TUM – FRM II

RRFM 2018 München | Stéphane Valance | CEA Cadarache

Project main facts





Project breakdown



Work package	Strategic objectives			
	Advance UMo fuel development	Assess U ₃ Si ₂ solution for HPRR	Diversify fuel supply for European MPRR	n: CE/
Manufacturing		robust and existing process for U ₃ Si ₂		0
		improvement of existing technology for U ₃ Si ₂		Jat
	improving UMo manufacturing technology			rdir
	control QA: UT measurements			0
UMo fuel comprehension	PIE analysis EMPIRE monolithic mini-plates			Ŭ
	thermo-mechanical modelling MAIA			
Fuel utilization in RR			EU MPRR fuel requirement assessment EU MPRR reliable and robust fuel supply FOAK controlled and standard fuel assemblies preliminary design	: LGI
	TRL assessment			0
Safety, licensing and Demonstration			general safety and licensing requirements scale 1 demonstration and qualification 4everTest	A
		high loaded U3Si2 evaluation - HiPROSIT		

(0) LEU context



LEU:

- **Prevent proliferation**;
- Enrichment below 20%.

How:

💌 Increase uranium density;

Ise of UMo or U_3Si_2 compounds.



(0) highlight: LEU manufacturing



UMo:

- Assessment of the UMo powder coating equipment (PVD & ALD)
- EMPIrE monolithic plates PIE
- Optimization of the PVD monolithic coating process and pilot equipment
 C2TWP for full-size plates
- Manufacturing of a thickness gradient in foils
- C2TWP on graded foils

UT QA measurement equipment

(1) UMo: background



FUTURE, BOL



FUTURE, EOL



UMo fuel types:

U 7% wght. Mo dispersion;U 10% wght. Mo monolithic.

UMo dispersion behavior:

- no barrier (FUTURE) Inter-Diffusion Layer (IDL) formation -> breakaway swelling;
- partial barrier (E-FUTURE) reduced IDL formation -> breakaway swelling;
- barrier (SELENIUM) scarse IDL formation-> accelerated swelling.



(1) UMo: Heracles-CP ∩ FOREvER



Examinations on UMo

X. Iltis et al., poster A0084;F. Vanni et al., poster A0121.

Irradiations

Stepnik et al., presentation A0120;

Solution Glagolenko et al., presentation A011.

(1) highlight: MAIA computations

MAIA code:

- **FE** computation of MTR fuel plates;
- Predefined meshes for flat and curved fuel plates;
- Material laws available for U₃Si₂ and UMo fuel core.

Utilization:

- Thermo-mechanical simulations of SEMPER-FIDELIS irradiations (UMo);
- \square Pre-dimensioning of HiPROSIT (U₃Si₂).

SEMPER-FIDELIS simulation objective:

- Compute fissile core temperature evolution during irradiation;
- Understand relationship between IL formation and temperature.





Temperature (°C)

(2) high loaded U₃Si₂ for HPRR



High loaded U₃Si₂ principle:

Higher plate thickness;
 Lower cladding thickness;
 Higher U₃Si₂ density in the Al matrix.

High loaded U₃Si₂ development:

- Manufacturability;
- 💌 Testing;
- Maptation to targeted research reactors.



(2) highlight: HiPROSIT irradiation



Irradiation HiPROSIT in the BR-2 reactor

4 full scale fuel plates;
 Maximum power 470 W.cm⁻²;
 Target BU up to 80% ²³⁵U consumption.

Tested parameters

Thinner cladding, down to 0.3 mm;
 Thicker fuel core, up to 0.7 mm;
 Higher uranium density, up to 5.6 g.cm⁻³.



(3) 4ever irradiation test in LVR15





A path toward fuel supply diversification:

Assess legal background and safety rules;

Design technically and economically viable substitution Fuel Assemblies (FA);

■ Manufacture and test under irradiation in LVR15 the designed FA \rightarrow 4EVER test;

Solution Post irradiation characterizations to validate its behavior under irradiation.

(3) highlight: design to cost



Main hypothesis (to be cost effective)

- Core and experimental load performances: at least, at the same level;
- Safety methodologies: no change of the current one;
- Main interfaces: Neither change of the control and shutdown systems components nor of the cooling systems, nor of the experimental devices, nor of the I&C, nor the core grid.

Key drivers

A good data gathering and synthesis;

 \square An innovative approach of the new fuel design based on U₃Si₂ proven technology.



Dissemination



Summer school

💌 Place

💌 Date

Content

XXX 🔊

💌 XXX

Picture of the intended location

Stay tuned!

Summary

H2020 project funded until 2021 for the development of LEU fuel for HPRR and MPRR.

Robust evaluation of substitution solutions for HPRR reactors.

Complementary to HERACLES-CP H2020 project.

Framework for the development of fuels for European MPRR.

Actions targeting every levels of development: design, test, examinations, manufacturability etc.





This project has received funding from the Euratom research and training programme 2014-2018 under grant agreement No 754378