



Development of an austenitic/martensitic gradient steel by additive manufacturing

F. Villaret, X. Boulnat, P. Aubry, D. Fabregue, Y. de Carlan

► To cite this version:

F. Villaret, X. Boulnat, P. Aubry, D. Fabregue, Y. de Carlan. Development of an austenitic/martensitic gradient steel by additive manufacturing. International Congress on Advances in Nuclear Power Plants (ICAPP - 2019), May 2019, Juan-Les-Pins, France. pp.1868 - 1879. cea-02339473

HAL Id: cea-02339473

<https://cea.hal.science/cea-02339473>

Submitted on 27 Nov 2019

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

000040 - Development of an austenitic/martensitic gradient steel by additive manufacturing

Flore Villaret^{1*}, Xavier Boulnat², Pascal Aubry³, Damien Fabrègue², Yann de Carlan¹

¹DEN-Service de Recherches Métallurgiques Appliquées (SRMA), CEA, université Paris-Saclay, F-91191, Gif-sur-Yvette, France

² Université de Lyon, INSA de Lyon, MATEIS CNRS UMR 5510, F-69621 Villeurbanne, France

³DEN-Service d'Études Analytiques et de Réactivité des Surfaces (SEARS), CEA, université Paris-Saclay, F-91191, Gif-sur-Yvette, France

* Corresponding Author, E-mail: flore.villaret@cea.fr

KEYWORDS: *additive manufacturing, powder metallurgy, gradient material*

In many applications, additive manufacturing techniques are rising to build, layer-by-layer, component with complex shapes and specific microstructures. With the Direct Metal Deposit (DMD) process, a nozzle delivers the powder directly to the molten pool, generated beneath the laser beam. An advantage of this process is the possibility to tune the material's composition, using different powder feeder, through the powder flow. Thus, it became possible to build composition gradient parts. Gradient components are studied for industrial applications such as functional materials ([1], [2]) or as a way to solve welding problems([3], [4]). In this study, we focused on a gradient from a 316L austenitic stainless steel to a 9Cr-1Mo martensitic steel. These steels are widely used for nuclear applications, and especially for fuel assemblies in Sodium Fast Reactors. Due to their chemical composition differences, welding them is uneasy, requiring filling metal and post-welding heat treatments [5].

The aim of this study is to compare microstructures obtained by traditional Tungsten Inert Gas with graded parts obtained by powder metallurgy, after Spark Plasma Sintering or additive manufacturing with Direct Metal Deposit process.

Microstructures are analyzed using Scanning Electron Microscope (SEM) and Electron BackScatter diffraction (EBSD) and correlated to thermokinetic calculations. The relationships between the mechanical behavior, the microstructures and the processes are discussed.

References

- 1) B. Heer and A. Bandyopadhyay, *Mater. Lett.*, vol. 216, pp. 16–19, 2018.
- 2) B. E. Carroll, R. A. Otis, J. P. Borgonia, J. O. Suh, R. P. Dillon, A. A. Shapiro, C. D. Hofmann, Z. K. Liu, A. M. Beese, *Acta Mater.*, vol. 108, pp. 46–54, 2016.
- 3) W. Li, S. Karnati, C. Kriewall, F. Liou, J. Newkirk, K. M. Brown Taminger, W. J. Seufzer, *Addit. Manuf.*, vol. 14, pp. 95–104, 2017.
- 4) T. Mukherjee, J. S. Zuback, W. Zhang, and T. DebRoy, *Comput. Mater. Sci.*, vol. 143, pp. 325–337, 2018.
- 5) H. Y. Lee, S. H. Lee, J. B. Kim, and J. H. Lee, *Int. J. Fatigue*, vol. 29, no. 9–11, pp. 1868–1879, 2007.