

Wavefield characteristics and spatial incoherency - a comparative study from Argostoli rock- and soil-site dense seismic arrays

Afifa Imtiaz, Vincent Perron, Fabrice Hollender, Pierre-Yves Bard, Cécile Cornou, Angkeara Svay, Nikos Theodoulidis

▶ To cite this version:

Afifa Imtiaz, Vincent Perron, Fabrice Hollender, Pierre-Yves Bard, Cécile Cornou, et al.. Wave-field characteristics and spatial incoherency - a comparative study from Argostoli rock- and soil-site dense seismic arrays. Bulletin of the Seismological Society of America, 2018, 108 (5A), pp.2839-2853. 10.1785/0120180025. cea-02339740

HAL Id: cea-02339740 https://cea.hal.science/cea-02339740

Submitted on 16 Mar 2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

1	Wavefield characteristics and spatial incoherency – a
2	comparative study from Argostoli rock- and soil-site dense
3	seismic arrays
4	by
5	A. Imtiaz ^{1,3} , V. Perron ^{2,3,6} , F. Hollender ² , P-Y. Bard ³ , C. Cornou ³ , A. Svay ⁴ , N. Theodoulidis ⁵
6	
7	Corresponding Author:
8	Afifa Imtiaz
9	Bureau de Recherches Géologiques et Minières (BRGM)
10	Seismic and Volcanic Risks Unit
11	Risks and Prevention Division
12	3, Avenue Claude Guillemin - BP 36009 - 45060 Orléans cedex 2, France
13	Tel : +33(0)2 38 64 30 95
14	E-mail : a.imtiaz@brgm.fr
15	ORCID iD: <u>https://orcid.org/0000-0001-6687-8690</u>
16	
17	⁽¹⁾ BRGM, F-45060 Orléans, France
18	⁽²⁾ CEA, DEN, F-13108 St Paul lez Durance Cedex, France
19	⁽³⁾ Univ. Grenoble Alpes, Univ. Savoie Mont-Blanc, CNRS, IRD, IFSTTAR, ISTerre,
20	Bâtiment OSUG C, CS 40700, 38058 GRENOBLE Cedex 9, France
21	(4) IMSIA, University Paris-Saclay, France
22	⁽⁵⁾ Institute of Engineering Seismology and Earthquake Engineering (ITSAK), GR-
23	55102 Thessaloniki, Greece
24	⁽⁶⁾ IRSN, F-92260 Fontenay-aux-Roses, France

25 ABSTRACT

26 The current article focuses on the results obtained from the analysis of seismic events recorded 27 by a dense array located on a rock site at Argostoli in the Cephalonia Island of Greece. The 28 objective of the study is threefold: (1) to explore to what extent the non-direct, diffracted surface waves influence the seismic wavefield at a rock site, (2) to investigate the loss of 29 30 coherency of ground motions, and (3) to compare the results with those from a previously 31 studied similar array located at an adjacent small, shallow sedimentary valley (soft-soil site). Both arrays consist of 21 velocimeters encompassing a central station in four concentric circles 32 with diameters ranging from 10 to 180 m at the soft-soil and 20 to 360 m at the rock site. The 33 34 seismic datasets under consideration include 40 or more events occurring around the site at epicentral distances up to 200 km having magnitudes ranging from 2 to 5. The seismic 35 36 wavefields at both sites are analyzed by using the MUSIQUE algorithm: the backazimuth and 37 slowness of the dominant incoming waves are extracted and the Love and Rayleigh waves are 38 identified. Lagged coherency is estimated from the dataset, and the results are averaged for station pairs located at four separation distance intervals, 10-20, 20-30, 30-40 and 80-90 m. 39 40 The results indicate that coherency at the rock site is, generally, larger than that from the soft-41 soil, especially at frequencies below 5 Hz. At soil site, lower coherency is observed for pairs along the valley-width direction while no such directional dependence is observed at the rock. 42 The wavefield analysis shows that whilst about 40-60% of the seismogram energy at the soft-43 soil could be associated to diffracted surface waves (Love and Rayleigh) appearing mainly 44 45 from the valley-width directions, only about 20% of energy at the rock site could be characterized as diffracted surface waves. Comparison with the widely-quoted parametric 46 models reveals that the observed decay of coherency at both sites has little correlation with 47 those from the models. These significant differences observed between the results of the rock 48 and soil array indicate that the spatial incoherency is largely site dependent and is likely to be 49 50 closely related with the formation of locally generated wavefield.

51

Keywords: Wavefield characteristics; Spatial Coherency; Dense Array; Rock Site; Soft-soil
 site; Cephalonia.

54 INTRODUCTION

55 The effects of spatial variability of earthquake ground motion (SVEGM), in other words the 56 amplitude and phase variability of ground motion observed at two adjacent positions, have 57 been of great interest for a long time in the design and analysis of large and extended structures. 58 Though such variation is, generally, attributed to the wave passage delay, spatial incoherence 59 and local site effects, the spatial incoherence caused by the effects of complex wave 60 propagation and scattering has increasingly caught interest of the research community. It is a 61 common practice to characterize the spatial phase variations by coherency functions from the 62 stochastic analysis of dense seismic arrays. These functions represent the degree of correlation between ground motion measurements at two adjacent positions as an exponential decay with 63 64 increasing frequency and interstation distance.

65

66 A great deal of existing literature into SVEGM has been devoted to the development of 67 coherency models (see Zerva and Zervas 2002 and Liao 2006 for a review). However, the generalizability of these models remains uncertain due to the lack of their association with the 68 69 physical site parameters. Much of the current literature is dedicated to the analysis of rather 70 large dimension arrays (>100 m), located mostly at soil sites, and relevant for distances longer than the dimensions of most structures. Besides, complex wave propagation and scattering 71 72 effects at rock-type ground conditions have received scant attention as the seismic wavefield is expected to be dominated by direct body waves at stiffer sites. As a result, there remains a 73 74 paucity of research on the physical implications of short-distance spatial incoherency from 75 rock-site dense arrays even though spatial incoherency has also been observed at rock sites 76 owing to geological complexities such as weathering and shallow fracturation (Somerville et al. 1991; Steidl et al. 1996). In reality, horizontally extended structures (e.g., bridges) may be 77 78 supported at different site conditions, soil or rock or a combination, and thus be exposed to

79 different degrees of differential motions. Therefore, extending our attention to rock sites 80 alongside soil sites could be instrumental in understanding the SVEGM as well as evaluating the site specific risk of infrastructures. The present study attempts to contribute to this area of 81 82 research by presenting the results obtained from the seismic events recorded at two nearby dense arrays, located at a rock and a soft-soil site, at Argostoli in the Cephalonia Island of 83 84 Greece. It aims at investigating to what extent non-direct, diffracted surface waves contribute 85 to the seismic wavefield at both sites, and at examining the site-dependence of the spatial variation. The part of the research concerning the soft-soil site is drawn from Imtiaz (2015) and 86 87 Imtiaz et al. (2014, 2015, 2017a, b). Hence, this paper first provides a brief literature review of the rock-site coherency models, presents the dense array deployed at Argostoli rock site, 88 89 focuses on the results obtained from the corresponding data analysis, and proceeds on their 90 comparison with those from the soil site.

91

92 The two dense arrays consist of 21 broadband velocimeters, placed in four circles, at diameters 93 20 to 360 m (rock) and 10 to 160 m (soft-soil), centered on a reference station. Two sets of earthquakes (40 events for the rock and 46 for the soft-soil array), with local magnitudes ML 94 2-5, occurring within an epicentral distance (R_{epi}) of 200 km, are utilized to estimate the 95 apparent propagation characteristics of the waves and to identify the energies carried out by 96 97 Love and Rayleigh waves. The 'lagged' coherency is calculated as a measure of random 98 variability of the Fourier phase between any two stations in the array. Median coherency iss obtained for four separation distance intervals (10-20, 20-30, 30-40, and 80-90 m), common 99 to both arrays, and compared with some widely-quoted coherency models developed for rock 100 101 and soil sites.

102 COHERENCY FROM ROCK SITES

103 In current literature, very few coherency models are available for rock sites (e.g. Cranswick 104 1988; Menke et al. 1990; Toksoz et al. 1991; Abrahamson 2007). Schneider et al. (1992) 105 compared coherency estimations from a set of rock- and soil-site arrays with the coherency 106 function developed by Abrahamson et al. (1991) based on a soil site data (LSST, Taiwan array) 107 for separation distance shorter than 100 m. The authors observed that the soil coherency fits 108 well with the LSST model while the rock coherency seems comparable only when the site is 109 not affected by topographic variations. Abrahamson (2007) studied the same set of arrays but 110 removed the ones affected by the topographic variations. The author compared the respective 111 average coherency from the soil, soft-rock and hard-rock sites, and observed a clear site dependence. At interstation distance 15–30 m, the coherency increases with the stiffness of the 112 site. At 50–70 m, the soil and soft-rock estimates become comparable and the hard-rock 113 114 remains higher. Zerva and Stephenson (2011) investigated seismic records from an array 115 located on a variable site condition (valley and soft-rock) and observed that the complex wave 116 propagation pattern affects not only the valley but also the surrounding soft-rock. The authors 117 then highlighted the significance of irregular subsurface topography and formation of surface 118 waves in the physical understanding of the spatial variation. Konakli et al. (2014) estimated coherency from the USGS Parkfield rock array for the 2004 Parkfield mainshock and compared 119 120 with some existing models. Their result revealed that the observed variability of coherency 121 decay rate, as a function of frequency and interstation distance, was not reproduced by the 122 semi-analytical model of Luco and Wong (1986). At smaller interstation distances (<100 m), 123 the estimates were lower than those from the empirical model of Ancheta et al. (2011), updated 124 from Abrahamson et al. (1991), and the trend reverses at longer distances (>300 m). The 125 authors concluded, once again, by indicating a rather complex dependence of coherency on 126 effects related to source, propagation, topography and site, and the difficulty associated with 127 the task of explaining them by means of general, simplified processes. In a recent study, Svay 128 et al. (2017) estimated plane-wave coherency from an another subset of data consisting of 129 smaller magnitude (M_L 2.7-3.6), local events (R_{epi} 10-30 km) from the Argostoli rock array and 130 observed that both the Luco and Wong (1986) and Abrahamson (2007) models do not provide 131 a satisfactory match with estimated coherency values. A better fit is obtained when site-specific 132 decay parameters are considered in the functional forms of the parametric models.

133 ARGOSTOLI DENSE SEISMIC ARRAYS

134 Located in the north-westernmost boundary of the Aegean plate, the Ionian Island of Cephalonia is considered to be one of the most active seismo-tectonic regions in Europe. The 135 136 high seismicity of the area is associated with the dextral Cephalonia Transform Fault (CTF), 137 situated in the northwestern boundary of the island (Figure 1a) and capable of generating earthquake magnitudes up to M = 7.4 (Louvari et al. 1999). The rate of seismic slip in the CTF 138 is observed to be varying from 7 to 30 mm/yr (Anzidei et al. 1996; Hollenstein et al. 2006). 139 140 Historical data show that more than 10 earthquakes of magnitudes between 6.5 and 7.5 occurred in the area between 1900 and 1998 causing major destruction. Two major earthquakes 141 142 (moment magnitude Mw 6.1 and 6.0, and hypocentral depth ~10 km) hit the area on January 26 and February 3, 2014 (Karakostas et al. 2015; Theodoulidis et al. 2016). These events were 143 144 associated with the CTF and occurred within 20 km distance of the Argostoli town, damaging 145 a significant number of engineering structures. They were also followed by numerous 146 aftershocks up to Mw 5.5. A post seismic campaign was conducted at Argostoli area (Figure 1a) within the framework of the SINAPS@ project, funded by the French Research Agency 147 148 (ANR). A dense two-dimensional (2D) dense array, referred as "rock array" in this work (Figure 1b,c), intended to study short distance spatial variability of ground motion, was 149 150 deployed on the rock formation from February 6 to March 10, 2014 (Perron et al. 2018). This

151 network complements the dataset recorded by a geometrically similar, smaller-size array, referred as "soft-soil array" here (Figure 1b,d), on the nearby small, shallow, sedimentary 152 153 valley of Koutavos-Argostoli. The array was operational from September 2011 to April 2012 154 under the framework of EU-NERA (European Union - Network of European Research 155 Infrastructures for Earthquake Risk Assessment and Mitigation) 2011–2014 project (Imtiaz 156 2015). The rock array was deployed on a Cretaceous massive limestone (karstified and fractured) formation located about 2 km southeast of the soft-soil array. Figure 1b displays the 157 158 geological formation of the study area after Cushing et al. (2016). Geophysical surveys led to 159 the determination of the V_{S30} (i.e., the harmonic mean of the shear-wave velocities over the 160 30 m of soil) as around 250 m/s for the soft-soil site, and 830 m/s for the rock site.

161

162 The rock array consists of 21 three-component (3C), broadband velocimeters (Güralp 163 CMG6TD sensors with 30 s eigenperiods with integrated digitizers) belonging to different 164 SINAPS@ partners (Perron et al. 2017). The stations are placed on the same geological unit, 165 along four circles of diameters 20, 60, 180 and 360 m around the central station BOR0 (Figure 1c). On each circle, the stations branch off from B0R0 in N67°E, N139°E, N218°E, N286°E 166 167 and N356°E directions. The signals are digitized at 200 samples per second; hence, the Nyquist frequency is 100 Hz. Figure 1d shows the configuration of the soft-soil array. This array also 168 169 consists of 21 3C, broadband velocimeters (Güralp CMG40T sensors with eigenperiods 170 between 30 and 60s) connected to Nanometrics Taurus digitizers, belonging to the French SISMOBRESIF national pool of portable seismic instruments. The stations are positioned in 171 four concentric circles, with diameters 10, 30, 80 and 160 m, around the central station A00. 172 173 Five stations, branching off from A00 in five directions, N39°E, N112°E, N183°E, N255°E and N328°E, are placed on each concentric circle. The resolvable frequency range for both the 174 175 arrays could be considered as 1–20 Hz for slowness over 0.0004 s/m.

176 Both arrays provided a rich database by recording more than thousand earthquakes. The rock 177 array recorded nearly 1850 good quality earthquakes with local magnitude ranging from 1 to 5, at epicentral distances up to 300 km, mainly corresponding to the seismic sequence of the 178 179 aforementioned two consecutive earthquakes occurred in 2014, including some tens of events 180 at greater distances and more varied azimuths (Hollender et al. 2015). A subset of 40 events 181 with very good signal to noise ratio, local magnitude (M_L) 2 to 5, hypocentral depth (H) 4 to 182 40 km, epicentral distance (R_{epi}) 5 to 200 km, recorded by at least 20 stations of the array, is selected for the analysis. The events are chosen such that a homogeneous distribution of 183 184 epicentral distance, magnitude and azimuthal coverage could be achieved, considering that most of the events occurred along the CTF in the west and some local $M_L>3.5$ events were 185 186 saturated. The origin time, location and the magnitude of the events have been taken from the 187 catalog of NOA (National Observatory of Athens) and Karakostas et al. (2015). The location 188 of the selected events are presented in Figure 2a, and their characteristics are provided in Table 189 1. It is to be noted that in this study, the entire seismogram (duration beginning from the P-190 wave arrival up to the end of coda) is used for the wavefield analysis while the time window 191 representing mainly the most energetic phase carried out by the S-wave is used for coherency 192 estimation. Both durations are also given in Table 1. Figure 2b presents the durations of the selected events for coherency analysis as a function of respective hypocentral distances. A 193 194 summary of the number of events grouped according to different parameters (distance, 195 magnitude, backazimuth) is given in Table 2. Finally, the results from the analysis of rock array data are compared to those from a set of 46 events with similar characteristics (ML 2-5 and Repi 196 up to 200 km) recorded by the soft-soil array. The details of this database is provided in Imtiaz 197 198 (2015) and (Imtiaz et al. 2017b).

200 WAVEFIELD ANALYSIS

201 The MUSIQUE algorithm (Hobiger et al. 2012, 2016) is used to perform the wavefield 202 characterization of the array data. MUSIQUE is a combination of the "classical" Multiple 203 Signal Characterization (MUSIC) (Schmidt 1986; Goldstein and Archuleta 1987) and the 204 quaternion-MUSIC (Miron et al. 2005, 2006) methods, that allows not only the extraction of 205 backazimuth and apparent phase velocity (or slowness) of the dominant waves crossing the 206 array but also their characterization as Love or Rayleigh waves. Detailed description of the 207 MUSIQUE algorithm for 3C signals is available in Hobiger (2011) and Hobiger et al. (2016). 208 Only a brief summary of the method is presented in the current article.

209

The basic principle of the method is to separate the signal and noise subspaces and then to 210 211 estimate the signal parameters. Let us assume a dataset recorded by an array of N single-212 component sensors. As a first step, MUSIQUE calculates the cross-correlation matrix (in time 213 domain) or cross spectral matrix (in frequency domain) for each frequency and time windows of interest, and defines the eigenstructure of the covariance matrix. The eigenvectors 214 215 corresponding to the K strongest eigenvalues define the signal subspace (K<N) while the N-K 216 weakest eigenvalues define the noise subspace. Then, from the set of array manifold vectors, 217 the vectors that give the minimum projection onto the noise subspace are determined through 218 the search of the maxima of the directional function (the so-called MUSIC spectrum). Once the 219 signal vectors are determined, propagation direction and phase velocity of the dominant signals 220 are computed as the functions of time and frequency. Quaternions, an extension of complex 221 numbers into four dimensions (e.g. Ward 1997), are then used to characterize polarization 222 parameters of an incident wave. The quaternion-MUSIC algorithm merges both the complexvalued data vectors of radial and vertical components into a single data matrix so that the phase 223 224 information and the sense of rotation of the particle motion remains naturally preserved, hence,

allowing the distinction between retrograde and prograde Rayleigh wave motions. Although the classical MUSIC is able to identify multiple sources, the MUSIQUE code is presently limited to a single wave contribution, i.e. to the most dominant source (K=1) as it requires projecting the horizontal signals with respect to the identified wave backazimuth in order to estimate the polarization parameters.

230

231 As a first step of the data analysis, the entire length of signal is divided into smaller sub-232 windows of five periods as a function of frequency. Here 200 log-based steps between 1 to 233 20 Hz frequency are used and the sub-windows are overlapped by 50%. A spectral averaging is done over five frequency samples centered on each frequency step in order to assure a well-234 235 conditioned covariance matrix. Then the slowness and backazimuth (θ) of the most dominant 236 incident wave for each sub-window of the signal is determined from the MUSIC spectrum. The 237 radial and transverse components are computed by projecting the east-west (EW) and north-238 south (NS) components of the signals along the identified backazimuth (θ) and its orthogonal 239 direction. During the post-processing, the results from the sub-windows containing energy less 240 than the median energy of all the analyzed windows of an event are filtered out. Additionally, 241 the sub-windows having signal to noise ratio less than 5 and slowness outside the range of 0.0004 to 0.008 s/m (apparent velocity 125 m/s to 2500 m/s) are also filtered out. A detailed 242 243 description of the post-processing calculations is given in Imtiaz (2015).

244

Figure 3 shows EW component of the velocity time series of an $M_L=3.5$ earthquake (ID # 11 in Table 1) recorded by all the stations of the rock array. The event occurred at a hypocentral deth (H) of 31 km, an epicentral distance (R_{epi}) 13 km and, and a backazimuth (θ) N348°E. Figure 4a illustrates the retrieved backazimuths of the dominant incident waves from all the analyzed sub-windows as a function of time. The colorbar corresponds to the 'normalized

energy' of the respective windows, defined as the energy carried out by the sub-window 250 251 divided by the squared Fourier amplitude. On this plot, the P and S wave arrivals and their 252 respective durations could be followed through the energy concentration of the results. It can 253 also be observed that the energetic incident waves are not necessarily arriving from the source 254 direction (N348°E, marked by the red horizontal line); they are rather scattered along other 255 directions even in the earlier part of the seismogram (<10 s). Figure 4b presents the 2D 256 histogram of backazimuth distribution as a function of frequency. In order to group the results, 257 72 grid points have been considered between N0°E and N360°E angles (interval = 5°) for the 258 backazimuth axis and 31 log-based grid points between 1 and 20 Hz for the frequency axis. 259 The colorbar indicates the summed 'normalized energy' of the analyzed sub-windows falling 260 into the backazimuth-frequency grids. The histogram demonstrates that most of the energetic 261 waves at frequencies lower than ~6 Hz are appearing from north to north-east (roughly N330°E 262 to N30°E), which corresponds mainly to the event's backazimuth direction. The scattered 263 energetic waves are observed at higher frequencies (>6 Hz).

264

Decomposition of diffracted surface waves

Next, the results corresponding to the direct arrivals (considered as waves coming from 265 266 backazimuth $\pm 20^{\circ}$ direction) are eliminated for each event in order to separate the diffracted 267 wavefield and the estimates from all the individual events are summed. During the wavefield analysis, the dominant incident waves are identified as Love or Rayleigh waves based on the 268 energy content of the analyzed signal window. A sub-window is characterized as Love- or 269 270 Rayleigh-dominant, respectively, when the estimated transverse energy or the summation of 271 the radial and vertical energy is more than 70% of the total energy of that window. If none of 272 these criteria is fulfilled, no wave is identified for the sub-window under consideration. In order 273 to summarize the observations from all the events and to focus on the surface wave 274 composition, only the results corresponding to the windows 'identified' as Love or Rayleigh are considered for further analysis. Hence, the 'non-identified' windows are also subtracted inthe process.

277

278 Figure 5a shows the summary of the backazimuth distribution of the entire diffracted wavefield (waves 'identified' as Love and Rayleigh + waves remained 'unidentified') from all the 40 279 280 events recorded by rock array. Same as Figure 4b, 72 grid points have been considered between 281 N0°E and N360°E angles (interval = 5°) for the backazimuth axis and 31 log-based grid points 282 between 1 and 20 Hz for the frequency axis. The colorbar indicates the summed 'normalized 283 energy' of all the sub-windows from the dataset falling into the backazimuth-frequency grids. 284 It seems that the diffracted waves are arriving approximately from the north-south direction 285 over the entire frequency range for the rock array. The summary of the diffracted waves 286 identified as Love and Rayleigh is presented in Figure 5b and Figure 5c, respectively. While a 287 weak dominance of Rayleigh waves arriving from the north-south direction is evident at higher 288 frequencies (>5 Hz), an even weaker dominance of Love waves from the north-east is observed 289 at lower frequencies (<5 Hz). On the contrary, the similar results of the wavefield analysis from the soft-soil array (Imtiaz et al. 2014) presented in Figure 5d-e show the predominance of 290 291 significant diffracted surface waves, propagating along SW-NE direction (Figure 5d), beyond 292 the fundamental frequency (~1.5 Hz) of the valley. The lower frequencies (1-3 Hz) seem to be dominated by Love waves (Figure 5e) while the higher frequencies by both Love and Rayleigh 293 294 waves (Figure 5f).

295

Figure 6a-d illustrate the arithmetic mean $\pm 1\sigma$ of diffracted and direct, Rayleigh and Love energy as a percentage of the 'total analyzed energy' (all direct and diffracted waves) for the rock and soft-soil array. On an average, about 20% of the 'total analyzed energy' from the rock array could be characterized as diffracted Love and Rayleigh waves (Figure 6a). Love wave 300 composition seems to be slightly higher than Rayleigh only up to ~2 Hz frequency. In case of 301 the soft-soil array (Figure 6b), the wavefield is found to be composed of a much higher 302 proportion of surface waves, average ranging from 40% to 60%, over the entire analyzed 303 frequency range. A clear frequency dependence of the energy distribution is also observed: 304 lower frequencies (1-2.5 Hz) are dominated by Love waves, while certain narrow bands of 305 higher frequencies are dominated either by Love or Rayleigh waves. Correlatively, only up to 5% and 5-10% of the 'total analyzed energy' could be characterized as direct surface waves 306 307 for the rock and soft-soil arrays, respectively (Figure 6c,d). At both sites, more than 80% of the 308 mean surface wave energy (Love + Rayleigh) correspond to the diffracted waves while only 309 around 20% to the direct waves (Imtiaz 2015; Sbaa et al. 2017).

310 COHERENCY ANALYSIS

311 *Estimation of lagged coherency*

312 Coherency is a complex-valued function and characterizes the variation in Fourier phases between two ground motions. By definition, lagged coherency is supposed to remove the 313 314 effects of systematic variation coming from the time delay in wave arrivals, known as the 'wave-passage effect'. Therefore, the two time histories under consideration are aligned using 315 316 the time lag that leads to the largest correlation of the motions. In this study, the records from 317 each station in the array are aligned with respect to the central station (B0R0 for the rock and 318 A00 for the soil array). However, no remarkable time lag (generally <2% of the coherency window) is observed for both arrays. The duration of the most energetic, S-wave dominated 319 320 signal window is selected for coherency analysis by visually inspecting the records of the 321 central station. Details of the time-window selection procedure and the coherency estimation 322 are provided in Imtiaz et al. 2017 (a, b).

The selected time windows of the signals are cut and tapered by using 5% cosine bell window at both ends. The cross- and auto-spectra of the motions are calculated and averaged over 11 frequency points by using a Hamming (M=5) window. Finally, the lagged coherency between a pair of stations is estimated as the modulus of the complex coherency, i.e., the ratio between the smoothed cross spectrum (\overline{S}_{jk}) of the pair of stations (j, k), normalized by the geometric mean of the smoothed power spectra at the respective stations (\overline{S}_{jj} , \overline{S}_{kk}), as function of the interstation distance (ξ) and frequency (1 to 25 Hz), and given by,

331

332
$$|\overline{\gamma}_{jk}(\xi, f)| = \frac{|\overline{S}_{jk}(f)|}{|\sqrt{\overline{S}_{jj}(f)\overline{S}_{kk}(f)|}}$$
(1)

333

The values of lagged coherency range from 0 to 1 for fully uncorrelated to fully correlated 334 motions. When the interstation distance or frequency tends to zero the estimates tend to 1. 335 336 Theoretically, at higher frequencies and larger interstation distances coherency tends to zero. 337 However, in actual calculations the modulus of the complex coherency tends to a constant 338 value significantly larger than zero due to the level of smoothing applied to the inherent noise 339 in the data. The median value of this constant is considered as 0.33 when an 11-point Hamming window is applied for frequency smoothing (Abrahamson 1992). As the coherency estimates 340 341 below this value are uninterpretable, it is termed as the 'resolvability threshold' in this article. 342

The lagged coherency estimated from the EW component of the velocity seismograms (Figure 3) of the event no.11 is shown in Figure 7a-d. The station pairs consist of the central station and the other stations located along the five array-branch directions (N 356, N 67, N 139, N 213 and N 286) on the concentric circles. For example, the station pairs considered in the Figure 7a are B0R0-B1R1, B0R0-B2R1, B0R0-B3R1, B0R0-B4R1 and B0R0-B5R1 (Figure 1c). Thus the four interstation or separation distances considered in Figure 7 correspond to the radii of the concentric circles in the array, 10, 30, 90 and 180 m. As expected, the coherency is
observed to decay with increasing frequency and separation distance. No clear variation is
observed along the different direction of the pairs at a certain separation distance.

352 *Median from the dataset*

As the variability of coherency estimates is skewed, it is preferable to perform the statistical analysis on the ATANH (or, tanh⁻¹) transformation in order to produce approximately normally distributed data (Harichandran 1991; Abrahamson et al. 1991). The 'median resolvability threshold' of lagged ATANH coherency is 0.34 when 11-point Hamming window is applied (Abrahamson 1992).

358

359 Coherency analysis from the soft-soil array (Imtiaz et al. 2017b) showed that when the median 360 coherency is derived by averaging all station pairs irrespective of their orientations, the two geometric horizontal components (EW, NS) as well as their rotation along any physical 361 direction result in almost similar estimates. The authors also suggested that the source related 362 363 parameters had negligible effect on the loss of coherency of the dataset. Therefore, the horizontal components of the ground motion are not rotated and simply the EW and NS 364 components are considered for presenting the results. Lagged coherency of the three 365 366 components from all the available pairs of stations (max. 210 pairs per event) is estimated for the entire dataset. Table 3 shows the number of 'ideally available' (assuming data from all the 367 21 stations in the array are available) pairs of stations per event for the groups of separation 368 369 distances between 10 and 100 m. Four separation distance ranges (10-20, 20-30, 30-40 and 370 80–90 m) that include maximum number of pairs from both arrays have been chosen to present 371 the results. Median of the coherency estimates from the pairs available at a given distance range 372 for a single event is defined as the 'individual median'. Then the 'global median' of the entire 373 dataset at that given separation distance range is derived by combining all the available pairs

from all the events. Table 4 shows the number of total pairs considered from the entire datasetfor the estimation of 'global median' coherency.

376

377 The average coherency estimates from the rock array in terms of the 'individual median' of each event (thin black curves) along with the 'global median' (thick black curve) of all events, 378 379 as a function of frequency, are presented in Figure 8a-d for the EW component and in Figure 380 8e-h for Z (vertical) components. The corresponding 'global median' from the soft-soil array 381 is also plotted in thick red curve. The measure of variability or standard deviation (σ) about the 382 respective 'global median' curve is also provided by dashed lines. Here the σ is calculated in terms of Median Absolute Deviation (MAD), defined as the median of the absolute deviations 383 384 (i.e., residuals) about the median of the observations (see Huber 1981; Imtiaz et al. 2017b). A 385 logarithmic scale is used for the frequency axis to highlight the results that are less affected by 386 the resolvability threshold. However, the estimated median curves are observed to be well 387 above the threshold. The coherency seems to be larger on rock than on the soil, at least up to 388 5 Hz for the EW and 10 Hz for the Z components, and at all separation distances.

389

390 A directional variation of coherency estimates, depending on the orientation of the station-391 pairs, was observed in the results from the soft-soil array (Imtiaz et al. 2017b). Therefore, 392 median coherency estimates from the horizontal components of the arrays are compared, by 393 grouping the pairs lying in five array-branch directions at different separation distances. The results from the EW component are shown in Figure 9a-d for the rock array and in Figure 9e-394 h for the soft-soil array. In case of the soft-soil array, a consistent directional dependence of 395 396 coherency is observed at all separation distances, the highest coherency being in the N 328 and the lowest in the N 255 directions corresponding to the valley-parallel and -perpendicular axes, 397

respectively (Imtiaz et al. 2017b). However, no remarkable orientation dependence ofcoherency is observed for the rock array.

400 COMPARISON WITH EXISTING PARAMETRIC MODELS

401 Selected parametric models

A great variety of functional forms of lagged coherency is available in the literature although very few are based on rock data. Some widely quoted parametric models are selected in this article in order to compare with the median estimates from Argostoli data. Two semi-empirical and two empirical models, applicable for short interstation distances (<100 m), pertinent to soil and rock sites, are chosen and briefly presented below:

407

408 (a) The semi-empirical model of Luco and Wong (1986): It is based on the analysis of shear
409 waves propagating through a random medium and expressed as a double exponential decay
410 function of interstation distance (ξ) in m and angular frequency (ω) in rad/sec,

(2)

411
$$|\gamma(\xi,\omega)| = \exp(-\alpha^2 \omega^2 \xi^2)$$

412 The coherency drop parameter is given by $\alpha = v/V_s$, where V_s is the average shear-wave 413 velocity of the medium along the wave travel-path and v is a constant related to the medium 414 properties. Typical values of α are suggested within 2×10^{-4} to 3×10^{-4} sec/m. In this study, rather 415 than estimating α from the dataset, the median value 2.5×10^{-4} sec/m is taken.

416

417 (b) The semi-empirical model of Menke et al. (1990): It is one of the very few rock site
418 coherency models available in the existing literature, expressed as an exponentially decaying
419 function of separation distance (ξ) in m and frequency (f) in Hz,

420
$$|\gamma(\xi,f)| = \exp(-\alpha f\xi)$$
 (3)

421 where, α value is proposed within the range of 4×10^{-4} to 7×10^{-4} sec/m. Again, the he median 422 value of $\alpha = 5.5 \times 10$ -4 sec/m is considered in this study. The functional form of this model is 423 almost similar to that of Luco and Wong (1986) except that the latter expresses a squared 424 exponential decay of coherency. The Menke et al. (1990) model is seemingly the square root 425 of the Luco and Wong. Hence, the Luco and Wong model shows a larger decrease at higher 426 frequencies and larger separation distance, but the decay starts relatively later as "alpha" 427 coefficient is smaller.

428

(c) The empirical model of Abrahamson (2007): Abrahamson proposed a purely empirical
plane-wave coherency model for rock sites based on 78 earthquakes recorded at the Pinyon
Flat array, which is expressed as,

$$|\gamma^{pw}(\xi, f)| = \left[1 + \left(\frac{f \tanh(a_1\xi)}{f_c(\xi)}\right)^{n_1(\xi)}\right]^{-1/2} \left[1 + \left(\frac{f \tanh(a_1\xi)}{a_2}\right)^{n_2}\right]^{-1/2}$$
(4)

433 The coefficients are given as:

434 $a_1=0.4$, $a_2=40$, $n_1(\xi)=3.8-0.04\ln(\xi+1)+0.0105[\ln(\xi+1)-3.6]^2$, $n_2=16.4$ and $f_c=27.9-4.82$ 435 $\ln(\xi+1)+1.24[\ln(\xi+1)-3.6]^2$ for the horizontal component; and 436 $a_1=0.4$, $a_2=200$, $n_1(\xi)=2.03+0.41\ln(\xi+1)-0.078[\ln(\xi+1)-3.6]^2$, $n_2=10$ and $f_c=29.2-5.20$

- 437 $\ln(\xi+1)+1.45[\ln(\xi+1)-3.6]^2$ for the vertical component.
- 438

The plane-wave coherency is calculated by taking the real part of the smoothed cross-spectrum after aligning the ground motions on the best plane-wave speed. As such, it includes the random variations in the wave passage effect and should be lower than the lagged coherency, especially at higher frequencies and longer interstation distances.

443

(d) The empirical model of Ancheta et al. (2011) : Abrahamson et al. (1991) proposed anempirical model based on the estimation of lagged coherency from 15 earthquakes recorded at

446 a small array (LSST) located at a soil site in Lotung, Taiwan. This model allows investigations 447 of coherency for the horizontal components of the ground motion and for station separation 448 distance smaller than 100 m. Ancheta et al. (2011) proposed a slight modification in the first 449 term of this model, by comparing an analysis from a set of events recorded by the Borrego 450 Valley differential array (BVDA) located on an alluvium site, in order to correct the negative 451 bias at separation distance (" ξ ") smaller than 30 m. The resulting model is described as,

452
$$|\gamma(\xi,f)| = \tanh\{(3.79 - 0.499 \ln(\xi)) \left[\exp\{(-0.115 - 0.00084\xi)f\} + \frac{f^{-0.878}}{3} \right] + 0.35 \}$$
 (5)

454 *Observation vs the selected parametric models*

455 The estimated median coherency from the Argostoli rock and soft-soil arrays are compared at 456 four separation distances with the aforementioned parametric models, and are illustrated in Figure 10a-d for the horizontal and in Figure 10e-h for the vertical component. Here the 457 458 horizontal coherency is the arithmetic mean of the EW and NS component estimates. Instead 459 of using the ATANH transformation, the results are presented in terms of coherency ($|\gamma|$) in order to facilitate the interpretation. The models are computed for distances 15, 25, 35 and 460 461 85 m. Note that the semi-empirical (Luco and Wong 1986; Menke et al. 1990) and empirical 462 plane-wave (Abrahamson 2007) coherency models approach zero while the lagged coherency 463 estimates from the data and the empirical model (Ancheta et al. 2011) tend to the resolvability 464 threshold at higher frequencies. Thus, they are not comparable at those frequencies.

465

The rock coherency seems to be in fair agreement with the models over all the frequencies at 10–20 m, and up to 3 Hz frequency at other distances. As interstation distance increases, the models tend to overestimate the actual observations. The coherency values are always overestimated by the Abrahamson's hard-rock model. This may be due to the fact that the Argostoli rock array is situated on a lightly softer formation (V_{s30}=830 m/s) compared to the 471 data the model is based on (V_{s30} =1030 m/s). However, the soil-site model of Ancheta et al. 472 (2011) also overestimates the rock array coherency at all the distances above 20 m.

473

474 One fundamental issue with the semi-empirical models is that they consider a constant decay 475 rate with the wavelength whereas the real data exhibit varying decay tendencies with respect 476 to frequency and interstation distance. Therefore, the double exponential decay of Luco and 477 Wong (1986) model is observed to fit very well with the rock estimates at 80–90 m (up to about 6 Hz frequency) but not at shorter interstation distances. At shorter distances, coherency from 478 479 the Argostoli data are observed to decay much faster compared with the semi-empirical models. 480 This issue is somewhat taken care of by the empirical models but the overall decay rate in the 481 data still remains faster than the models. Coherency estimates from the Argostoli soil array 482 seems to be relatively poorly predicted by all the models. At shorter interstation distances (up 483 to 40 m) and higher frequencies (>5 Hz) the observed rock coherency is, surprisingly, slightly 484 lower than the soil. This could be attributed to the soil heterogeneities associated with the rock 485 site (karst filled with decalcification clay, fractured zone) whose characteristic "wavelength" 486 of variation is rather weak (metric to decametric).

487

Similar conclusions could be drawn for rock array data in case of the vertical component (Figure 10e-h). However, the vertical coherency from soil array seems to be decaying at a much faster rate up to about 7–8 Hz and shows a reverse tendency afterwards, especially at shorter interstation distances (10–40 m). This increasing trend is totally absent in the rock data. A possible explanation could be that the vertical coherencies at the soil site might be increased at some higher frequencies because of the presence of converted S-P waves or Rayleigh waves with higher phase velocities.

495 DISCUSSION AND CONCLUSIONS

496 The current study performs a twin analysis of wavefield characterization and spatial 497 incoherency of seismic motion recorded at two dense arrays of stations, one located on a rock 498 site, the other on a soft-soil site. As for the rock array, a large number (40) of small to moderate, 499 shallow, local and regional events with relatively even distribution in magnitude, distance and 500 backazimuth around the site, are analyzed. The loss of coherency is estimated for interstation 501 distance ranging from 10 to 360 m. The median of the estimates at different interstation 502 distance ranges (<100 m) have been examined and compared with those estimated from a 503 similar dataset recorded at a nearby soil site as well as with some of the existing parametric 504 models. The key results derived from the first part of the work, that is, the analysis of the 505 wavefield composition, reveal that some wave scattering over the frequency range of 1–20 Hz 506 is arriving from the north-south and north-east directions of the rock site for almost all the 507 events. However, only 20% of the total seismogram energy could be associated to diffracted 508 surface waves (Love and Rayleigh). As for the soft-soil array, about 40–60% of the analyzed 509 seismogram energy could be characterized as diffracted surface waves associated to 2D or 3D 510 geometrical effects, appearing mainly from the valley-width directions, with clear frequency-511 dependent dominance of Love and Rayleigh waves (Imtiaz et al. 2014). Besides, more than 80% of the total surface wave energy is observed to be carried out by the diffracted waves at 512 513 both sites. Hence, it is evident that the formation of diffracted surface waves is much more 514 significant, especially on the sedimentary valley (soft-soil site) compared to the rock site, and 515 may play an important role in causing the higher loss of coherency and its directional variability. 516

517

In the second part of the work, the estimated median lagged coherency from the rock dataexhibits very similar decaying tendencies for all the three components (EW, NS and Z). The

520 coherency is also found to be, generally, higher than that from the nearby soil site. However, 521 at shorter interstation distances and higher frequencies, rock coherency seems to be slightly 522 lower than that of soil. This could likely be attributed to the karstic-type weathering of the 523 Cretaceous limestone of the investigated rock site. This weathering shows strong lateral 524 lithological variation, with alternation at metric to decametric scale, of massive outcropping 525 limestone areas with zones dominated by decalcifying clay content. Further investigation is 526 suggested to better quantify this observation. The directional variability of lagged coherency, 527 depending on the orientation of the station pairs, observed at the soft-soil site appears to be 528 negligible for the rock site. Unlike the soft-soil site, coherency from vertical component seems 529 to be comparable with the horizontal at the rock site. Comparison of the median coherency 530 estimated from the arrays with the empirical models does not show any consistent correlation. 531 Overall, the rock coherency is overestimated by all the parametric models even by the empirical 532 one based on the soil data. Apparently, the decay rate of lagged coherency, as a function of 533 frequency, seems to be not only site dependent but also interstation distance dependent. The 534 fastest decay rate from the Argostoli data (both soft-soil and rock sites) is not well-captured by 535 the empirical models. On the other hand, the variability in the decay rate, especially with 536 respect to the interstation distance, is not addressed by the semi-empirical models. The findings of the present work reaffirm the site dependent nature of spatial variation and emphasize the 537 538 need for more rigorous efforts on studying different sites in order to better understand the 539 spatial variability of ground motion.

540 DATA AND RESSOURCES

The data used in the present work are open. The data from the rock and soft-soil sites can be
obtained on the data repositories detailed in Perron et al. (2017) and Theodoulidis et al. (2017),
respectively.

544 ACKNOWLEDGEMENTS

This work was carried out under the SINAPS@ project that receives French funding managed 545 by the National Research Agency under the program "Future Investments" (SINAPS@ 546 547 ANR-11-RSNR-0022). SINAPS@ is "Seism Institute" reference: а project (http://www.institut-seism.fr/en/). We would like to thank all the contributors of this work, 548 especially for helping on the field during the SINAPS@ post-seismic campaign, Régis 549 550 Cottereau (ECP), Marc Cushing (IRSN), Alberto Frau (CEA/EMSI), Sébastien Hok (IRSN), Philippe Langlaude (CEREMA), Aurore Laurendeau (CEA/LDG), Armand Mariscal (ISTerre) 551 552 and Alexandros Savvaidis (EPPO-ITSAK), as well as our local help on the Cephalonia Island,

553 Agis Konidaris (TEI) and Chrisostomos Andreou.

554 **REFERENCES**

- Abrahamson NA (2007) Program on Technology Innovation: Effects of Spatial Incoherence
 on Seismic Ground Motions. Rpt. No. EPRI 1015110, Palo Alto, CA
- 557 Abrahamson NA (1992) Spatial Variation of Earthquake Ground Motion for Application to
- 558 Soil-Structure Interaction. Rpt. No. EPRI TR-100463, Tier 1, Palo Alto, CA
- Abrahamson NA, Schneider JF, Stepp JC (1991) Empirical Spatial Coherency Functions for
 Application to Soil-Structure Interaction Analyses. Earthq Spectra 7:1–27. doi:
 10.1193/1.1585610
- 562 Ancheta TD, Stewart JP, Abrahamson NA (2011) Effects of Surface Geology on Seismic
- Motion. In: 4th IASPEI / IAEE International Symposium, University of California Santa
 Barbara. California,
- Anzidei M, Baldi P, Casula G, et al (1996) Repeated GPS surveys across the Ionian Sea:
 evidence of crustal deformations. Geophys J Int 127:257–267. doi:
 https://doi.org/10.1111/j.1365-246X.1996.tb04718.x
- 568 Cranswick E (1988) The information content of high-frequency seismograms and the near569 surface geologic structure of "hard rock" recording sites. Pure Appl Geophys PAGEOPH
 570 128:333–363. doi: 10.1007/BF01772604
- 571 Cushing EM, Hollender F, Guyonnet-Benaize C, et al (2016) Close to the lair of Odysseus
 572 Cyclops : the SINAPS@ postseismic campaign and accelerometric network installation
 573 on Kefalonia island Site effect characterization experiment. In: McCalpin J, Gruetzner C
- (eds) Proceedings of the 7th INQUA on Paleoseismology, Active Tectonics and
 Archeoseismology, Crestone, Colorado, USA, 30 May 3 June.
- 576 Goldstein P, Archuleta RJ (1987) Array analysis of seismic signals. Geophys Res Lett I4:13–
 577 16.
- 578 Harichandran RS (1991) Estimating the spatial variation of earthquake ground motion from

- 579 dense array recordings. Struct Saf 10:219–233.
- Hobiger M (2011) Polarization of surface waves : characterization, inversion and application
 to seismic hazard assessment. Université de Grenoble
- Hobiger M, Cornou C, Bard P-Y, et al (2016) Analysis of seismic waves crossing the Santa
 Clara Valley using the three-component MUSIQUE array algorithm. Geophys J Int
 207:439–456. doi: 10.1093/gji/ggw289
- 585 Hobiger M, Le Bihan N, Cornou C, Bard P-Y (2012) Multicomponent Signal Processing for
- 586 Rayleigh Wave Ellipticity Estimation Application to Seismic Hazard Assessment. IEEE
 587 Signal Process Mag 29:29–39–29–39.
- 588 Hollender F, Perron V, Imtiaz A, et al (2015) Close to the lair of Odysseus Cyclops : the
- 589 SINAPS@ postseismic campaign and accelerometric network installation on Kefalonia
- Island. In: Proceedings of the 9th Colloque National AFPS 2015, Marne-La-Vallée,
 France, 30 November 2 December.
- 592 Hollenstein C, Geiger A, Kahle H-G, Veis G (2006) CGPS timeseries and trajectories of crustal
- 593 motion along theWest Hellenic Arc. Geophys J Int 164:182–191. doi:
 594 https://doi.org/10.1111/j.1365-246X.2005.02804.x
- 595 Huber P (1981) Robust statistics. New York: John Wiley
- 596 Imtiaz A (2015) Seismic wave field, spatial variability and coherency of ground motion over
- short distances : near source and alluvial valley effects. PhD Thesis. Université Grenoble
- Alpes, English. <NNT: 2015GREAU002>. <tel-01148138>. https://tel.archivesouvertes.fr/tel-01148138
- 600 Imtiaz A, Cornou C, Bard P-Y (2017a) Sensitivity of Ground Motion Coherency to the Choice
- of Time Windows from the Argostoli Dense Seismic Array. Bull Earthq Eng (under Rev0:1–30.
- 603 Imtiaz A, Cornou C, Bard P-Y, Hobiger M (2014) Diffracted Wave Field And Coherency

Analysis: An Example From Dense Array Network In Argostoli Basin, Cephalonia,
Greece. In: Proceedings of the Second European Conference on Earthquake Engineering
and Seismology (2ECEES), Istanbul, Turkey, 24-29 August. p 12, Paper # 2351

Imtiaz A, Cornou C, Bard P-Y, Zerva A (2017b) Effects of site geometry on short-distance
spatial coherency in Argostoli, Greece. Bull Earthq Eng 1–35. doi:
https://doi.org/10.1007/s10518-017-0270-z

- Imtiaz A, Cornou C, Bard P-Y, Zerva A (2015) Spatial coherence of seismic ground motion
 and geometric structure of the sub-surface: an example in Argostoli, Greece. In:
 Proceedings of the 9th Colloque National AFPS 2015, Marne-La-Vallée, France, 30
 November 2 December.
- Karakostas V, Papadimitriou E, Mesimeri M, et al (2015) The 2014 Kefalonia Doublet (M6.1
 and M6.0), Central Ionian Islands, Greece: seismotectonic implications along the
 Kefalonia transform fault zone. Acta Geophys 63:1–16. doi: 0.2478/s11600-014-0227-4
- 617 Konakli K, Der Kiureghian A, Dreger D (2014) Coherency analysis of accelerograms recorded
- by the UPSAR array during the 2004 Parkfield earthquake. Earthq Eng Struct Dyn
- 619 43:641–659. doi: 10.1002/eqe.2362
- Louvari E, Kiratzi A, Papazachos BC (1999) The Cephalonia Transform fault and its extension
 to western Lefkada Island (Greece). Tectonophysics 308:223–236–223–236.
- Luco J, Wong H (1986) Response of a rigid foundation to a spatially random ground motion.
 Earthq Eng Struct Dyn 14:891–908.
- 624 Menke W, Lerner-Lam AL, Dubendorff B, Pacheco J (1990) Polarization and coherence of 5
- to 30 Hz seismic wave fields at a hard-rock site and their relevance to velocity
 heterogeneities in the crust. Bull Seism Soc Am 80:430–449.
- 627 Miron S, Le Bihan N, Mars J (2005) High resolution vector-sensor array processing using628 quaternions.

- Miron S, Le Bihan N, Mars J (2006) Quaternion-MUSIC for vector-sensor array processing.
 IEEE Trans Signal Process 54:1218–1229.
- Perron V, Hollender F, Mariscal A, et al (2018) Accelerometer, velocimeter dense-array, and
 rotation sensor datasets from the Sinaps@ post-seismic survey (Cephalonia 2014-2015
 aftershock sequence). Seism Res Lett (in press):0–0.
- 634 Sbaa S, Hollender F, Perron V, et al (2017) Analysis of rotation sensor data from the Sinaps@
- 635 Kefalonia (Greece) post-seismic experiment Link to surface geology and wave-field
- 636 characteristics. Earth, Planets Sp. doi: https://doi.org/10.1186/s40623-017-0711-6
- 637 Schmidt RO (1986) Multiple emitter location and signal parameter estimation. IEEE Trans
 638 Antennas Propag 34:276–280–276–280.
- 639 Schneider JF, Stepp JC, Abrahamson NA (1992) The spatial variation of earthquake ground
 640 motion and effects of local site conditions. Proc theTenth World Conf Earthq Eng Madrid,
 641 Spain 2:967–972.
- Steidl JH, Tumarkin AG, Archuleta RJ (1996) What is a reference site? Bull Seismol Soc Am
 86:1733–1748.
- 644 Svay A, Perron V, Imtiaz A, et al (2017) Spatial coherency analysis of seismic ground motions
- 645 from a rock site dense array implemented during the Kefalonia 2014 aftershock sequence.
- Earthq Eng Struct Dyn. doi: 10.1002/eqe.2881
- 647 Theodoulidis N, Cultrera G, Cornou C, et al (2017) Basin effects on ground motion: the case
- of a high-resolution experiment in Cephalonia (Greece). Bull Earthq Eng. doi:
 https://doi.org/10.1007/s10518-017-0225-4
- 650 Theodoulidis N, Karakostas C, Lekidis V, et al (2016) The Cephalonia, Greece, January 26
- (M6.1) and February 3, 2014 (M6.0) earthquakes: near-fault ground motion and effects
- on soil and structures. Bull Earthq Eng 14:1–18. doi: 10.1007/s10518-015-9807-1
- Toksoz MN, Dainty AM, Charrette III EE (1991) Spatial variation of ground motion due to

- lateral heterogeneity. Struct Saf 10:53–77.
- 655 Zerva A, Stephenson WR (2011) Stochastic Characteristics of Seismic Excitations at a Non-
- Uniform (Rock and Soil) Site. Soil Dyn Earthq Eng 31:1261–1284.

657 LIST OF FIGURE CAPTIONS

Figure 1 : Location of the study area and the arrays. (a) The Argostoli study area in the
Cephalonia Island. (b) Two arrays on the geological map of the area (Cushing et al. 2016).
Layout of the (c) rock and (d) soft-soil array.

Figure 2 : Dataset recorded by the rock-site array. (a) Location of the selected events with
respect to the site. The white circles show the other events recorded by the array. (b) Duration
of the selected time windows for coherency analysis.

Figure 3 : EW component of the velocity time series from an earthquake (ID #11 in Table 1: $M_L = 3.5$, Baz= N 348, $R_{epi} = 13$ km, H=31 km) recorded by the stations in the array. The time window between the red lines are considered for the coherency analysis of the event.

Figure 4 : Backazimuth distribution of the dominant incoming waves from the event no. 11

(Table 1) as a function of (a) time and (b) frequency. Red line marks the event-backazimuth.

669 Figure 5 : Cumulative histogram of the backazimuth, extracted from the wavefield analysis of

670 the selected dataset, considering the entire diffracted wavefield, and diffracted waves identified

as Love and Rayleigh waves, respectively, for the (a)-(c) rock and (d)-(f) soft-soil array.

Figure 6 : Repartition of energy (mean $\pm 1\sigma$) carried out by identified Rayleigh (R) and Love (L) waves, from the wavefield analysis of the selected dataset, considering the (a)-(b) diffracted and (c)-(d) direct waves, for the rock and soft-soil array. Here, the waves coming from the source-backazimuth $\pm 20^{\circ}$ direction are represented as the direct waves and the rest are considered as the diffracted waves.

Figure 7 : Lagged coherency estimated from the EW component of velocity time series (Figure
3) of the event no. 11 recorded by the rock array. Here, coherency is presented for the pairs
between the central station (B0R0 in Figure 1c) and the other stations lying along five arraybranch directions at four separation distances (a) 10 m, (b) 30 m, (c) 90 m and (d) 180 m.

681 Figure 8 : Median ATANH coherency estimated from the (a)-(d) EW and (e)-(h) Z component 682 of the velocity time series at four separation distances. The corresponding lagged coherency 683 values are marked at the right-side axis. Thin grey curves represent the 'individual median' of 684 the events recorded by the rock array and thick black curves represent their 'global median'. Red thick curves show the 'global median' estimated from the dataset recorded by the soft-soil 685 686 array. The dashed curves show the respective $\pm 1\sigma$ bound of the 'global median' ATANH coherency for the two arrays. Grey horizontal lines mark the coherency resolvability threshold. 687 688 Figure 9 : EW component of the 'global median' ATANH coherency, considering only the 689 station pairs lying along the five array-branch directions at four separation distances, from the 690 datasets recorded by the (a)-(d) rock and (e)-(h) soft-soil arrays.

Figure 10 : Comparison of the 'global median' coherency estimated from Argostoli rock and soft-soil arrays with the existing semi-empirical ('LW 1986' for Luco and Wong 1986; 'M 1990' for Menke et al. 1990) and empirical ('A 2007' for Abrahamson 2007; 'A 2011' for Abrahamson et al. 2011) coherency models for the (a)-(d) horizontal and (e)-(h) vertical component of the ground motion at four separation distances.

697 AUTHORS' AFFILIATIONS, ADDRESSES

- 698 1. Afifa Imtiaz
- 699 BRGM, F-45060 Orléans, France
- 700 a.imtiaz@brgm.fr
- 701

702 2. V. Perron

- 703 CEA, DEN, F-13108 St Paul lez Durance Cedex, France
- 704 Univ. Grenoble Alpes, Univ. Savoie Mont-Blanc, CNRS, IRD, IFSTTAR, ISTerre, Bâtiment
- 705 OSUG C, CS 40700, 38058 Grenoble Cedex 9, France
- 706 IRSN, F-92260 Fontenay-aux-Roses, France
- 707 vincent.perron.mail@gmail.com
- 708
- 709 3. F. Hollender
- 710 CEA, DEN, F-13108 St Paul lez Durance Cedex, France
- 711 fabrice.hollender@cea.fr
- 712

713 4. P-Y. Bard

- 714 Univ. Grenoble Alpes, Univ. Savoie Mont-Blanc, CNRS, IRD, IFSTTAR, ISTerre, Bâtiment
- 715 OSUG C, CS 40700, 38058 Grenoble Cedex 9, France
- 716 pierre-yves.bard@univ-grenoble-alpes.fr
- 717 718 4. C. Cornou
- 719 Univ. Grenoble Alpes, Univ. Savoie Mont-Blanc, CNRS, IRD, IFSTTAR, ISTerre, Bâtiment
- 720 OSUG C, CS 40700, 38058 Grenoble Cedex 9, France
- 721 cecile.cornou@univ-grenoble-alpes.fr
- 722
- 723 6. A. Svay
- 724 IMSIA, University Paris-Saclay, France
- 725 angkeara.svay@polytechnique.edu
- 726
- 727 7. N. Theodoulidis
- 728 Institute of Engineering Seismology and Earthquake Engineering (ITSAK), GR-55102
- 729 Thessaloniki, Greece
- 730 ntheo@itsak.gr

731 TABLES

ID	YY-MM-DD_hhmmss	PGV (m/s)	M _L	H (km)	R _{epi} (km)	Baz (N°)	Ts (s)	T (s)	Missing station(s)
1	2014-02-06_180549	1.918	3.9		16.3	299.9	2.21	26	-
23	2014-02-07_012153	1.134	4.2			80.5	6.62		-
		2.295	3.5	18	16.4	267.7	1.79		-
4		0.038	2.4			268.2	2.22		-
5	_		2.6			93.9			-
6			2.5			240.0	1.54		B2R3
7			3.1				2.39		-
8	—		3.2		10.6	264.6	1.91		-
9			2.7			244.0	1.77		-
10	—		2.8			81.2			-
11			3.5			348.9	2.83		B2R3
12	—		2.6			3.5			
13	_		2.0						B2R3
14			2.4			230.4			B2R3
15			2.6			342.6	2.09		-
16	—		2.7			240.7	2.79		-
17	—		2.6			8.8	2.79		-
18			3.0		9.7	7.7	2.53		B2R4
19	_	0.020	2.4			134.8			-
20			2.1			6.1	4.36		B2R2
21			2.7			145.4			-
22			1.9		11.8				-
23	_		2.5			101.1	5.87		-
24			2.9						-
25			2.6			251.1	1.96		-
26			2.7		53.3	359.9	3.36		-
27			3.4		175.0	87.6			
28			1.7			92.7	3.6		-
29			2.0			5.4			-
30	—		2.2			126.5			-
31	—		3.3			139.5			-
32	_		2.8			348.2			-
33			2.8						-
34			3.4			252.2	3.13		-
35			2.7		43.3	358.7	2.59		-
36			2.0			136.0	2.48		
37			3.9			145.0	15		-
38			2.2		39.0	239.1	3.2		-
39		0.032	2.5						
40	2014-03-10_055054	0.033	2.0	7	27.1	10.9	2.12	21	B1R4

732 Table 1: Characteristics¹ of the selected events from the rock array (Figure 1 c) data

¹ ID is the earthquake index, YY-MM-DD_hhmmss is the date and time of the earthquake occurrence, PGV is the Peak Ground Velocity, M_L is the local magnitude, H is the hypocentral depth, R_{epi} is the epicentral distance, Baz is the earthquake backazimuth, Ts is the duration of the time window for coherency estimation and T is the signal duration for wavefield analysis.

733 Table 2: The distribution of backazimuth, epicentral distance and magnitude of the selected

Backazimuth	Nb. of	Epicentral	Nb. of	Magnitude	Nb. of
quadrant	events	Distance (km)	events	(M_L)	events
NE	11	0-30	9	~2-3	29
NW	12	30–60	19	3–4	10
SE	10	60-100	5	4-5	1
SW	7	100-200	7		
Total	40		40		40

734 dataset from the rock array

735

- Table 3: Number of station pairs ideally available, when no station is missing, per event at
- 737 different separation distances (up to 100 m) for the rock and soft-soil arrays

Separation	10-20	20-30	30-40	40–50	50-60	60–70	70-80	80–90	90–100
Distance (m)									
Rock Array	19	15	16	0	7	3	2	24	15
Soft-soil Array	33	10	31	19	10	5	43	12	15


738

739 Table 4: Total number of actually available station pairs (considered for the median estimation)

at the selected four separation distances for the rock and soft-soil arrays.

Separation Distance (m)	10-20	20–30	30–40	80-90
Rock Array (total pairs from 40 events)	759	597	636	928
Soft-soil Array (total pairs from 46 events)	1574	414	1241	430

742 FIGURES



743

Figure 1 : Location of the study area and the arrays. (a) The Argostoli study area in the
Cephalonia Island. (b) Two arrays on the geological map of the area (Cushing et al. 2016).
Layout of the (c) rock and (d) soft-soil array.






Figure 2 : Dataset recorded by the rock-site array. (a) Location of the selected events with

respect to the site. The white circles show the other events recorded by the array. (b) Duration

751 of the selected time windows for coherency analysis.




Figure 3 : EW component of the velocity time series from an earthquake (ID #11 in Table 1: $M_L = 3.5$, Baz= N 348, $R_{epi} = 13$ km, H=31 km) recorded by the stations in the array. The time window between the red lines are considered for the coherency analysis of the event.









Figure 4 : Backazimuth distribution of the dominant incoming waves from the event no. 11










Figure 6 : Repartition of energy (mean $\pm 1\sigma$) carried out by identified Rayleigh (R) and Love (L) waves, from the wavefield analysis of the selected dataset, considering the (a)-(b) diffracted and (c)-(d) direct waves, for the rock and soft-soil array. Here, the waves coming from the source-backazimuth $\pm 20^{\circ}$ direction are represented as the direct waves and the rest are considered as the diffracted waves.

770

- 771
- 772
- 773




Figure 7 : Lagged coherency estimated from the EW component of velocity time series (Figure
3) of the event no. 11 recorded by the rock array. Here, coherency is presented for the pairs
between the central station (B0R0 in Figure 1c) and the other stations lying along five arraybranch directions at four separation distances (a) 10 m, (b) 30 m, (c) 90 m and (d) 180 m.




Figure 8 : Median ATANH coherency estimated from the (a)-(d) EW and (e)-(h) Z component of the velocity time series at four separation distances. The corresponding lagged coherency values are marked at the right-side axis. Thin grey curves represent the 'individual median' of the events recorded by the rock array and thick black curves represent their 'global median'. Red thick curves show the 'global median' estimated from the dataset recorded by the soft-soil array. The dashed curves show the respective $\pm 1\sigma$ bound of the 'global median' ATANH coherency for the two arrays. Grey horizontal lines mark the coherency resolvability threshold.




Figure 9 : EW component of the 'global median' ATANH coherency, considering only the
station pairs lying along the five array-branch directions at four separation distances, from the
datasets recorded by the (a)-(d) rock and (e)-(h) soft-soil arrays.




Figure 10 : Comparison of the 'global median' coherency estimated from Argostoli rock and soft-soil arrays with the existing semi-empirical ('LW 1986' for Luco and Wong 1986; 'M 1990' for Menke et al. 1990) and empirical ('A 2007' for Abrahamson 2007; 'A 2011' for Abrahamson et al. 2011) coherency models for the (a)-(d) horizontal and (e)-(h) vertical component of the ground motion at four separation distances.