



**HAL**  
open science

## Core@shell silicon-carbon nanoparticles with a tunable shell thickness: performances as battery anodes

Antoine Desrues, John Alper, Florent Boismain, Cédric Haon, Sylvain Franger, Nathalie Herlin-Boime

### ► To cite this version:

Antoine Desrues, John Alper, Florent Boismain, Cédric Haon, Sylvain Franger, et al.. Core@shell silicon-carbon nanoparticles with a tunable shell thickness: performances as battery anodes. EMRS Fall Meeting, Sep 2018, Varsaw, Poland. cea-02340324

**HAL Id: cea-02340324**

**<https://cea.hal.science/cea-02340324>**

Submitted on 30 Oct 2019

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

## **Core@shell silicon-carbon nanoparticles with a tunable shell thickness: performances as battery anodes**

Antoine Desrues, John P. Alper, Florent Boismain, Cédric Haon, Sylvain Franger, Nathalie Herlin-Boime

Symposium: Battery and energy storage devices

Nanometric silicon appears as an interesting candidate to improve the capacity of lithium-ion batteries anodes because its theoretical specific capacity is over 10 times that of current commercial graphite electrodes. A major issue with nanosilicon anodes is the continuous formation of solid electrolyte interphase (SEI) due to the significant volume changes in the material during lithiation-delithiation. Coating the silicon surface with carbon has proved to protect it, as a more stable SEI is obtained.

For this purpose, we synthesize core@shell silicon-carbon nanoparticles by using a double-stage laser pyrolysis reactor [1]. This gas-phase technique allows one-step synthesis of a silicon core coated by a carbon shell. The size and the size distribution, as well as the shell's thickness, can be controlled by the modification of parameters. This wall-less process leads to clean interfaces.

In this work the synthesis of carbon coated crystalline nanosilicon (30 nm) with various carbon contents, up to 20 % w/w, will be presented. These Si@C particles present a clear silicon-carbon interface as shown by STEM-EELS. The galvanostatic performance comparison indicates that the coulombic efficiency is improved by a greater carbon content and power rate experiments indicate that an optimum exists. Finally, by using electrochemical impedance spectroscopy (EIS), a comparison of SEI resistances for coated and non-coated particles will be presented.

[1] Sourice et al, ACS Appl. Mater. Interfaces 2015