

ZnFe_2O_4 and ZnO/Fe_2O_3 nanoparticles as anode materials for lithium-ion batteries: understanding of the lithium storage mechanism

Samantha Bourrioux, Yann Leconte, Moulay Tahar Sougrati, Lorenzo Stievano, Laure Monconduit, Zhichuan Xu, Madhavi Srinivasan, Alain Pasturel

► To cite this version:

Samantha Bourrioux, Yann Leconte, Moulay Tahar Sougrati, Lorenzo Stievano, Laure Monconduit, et al.. ZnFe_2O_4 and ZnO/Fe_2O_3 nanoparticles as anode materials for lithium-ion batteries: understanding of the lithium storage mechanism. ECerS 2017, Jul 2017, Budapest, Hungary. cea-02341796

HAL Id: cea-02341796 https://cea.hal.science/cea-02341796

Submitted on 31 Oct 2019

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

ZnFe₂O₄/C NANOPARTICLES BY LASER PYROLYSIS: NEW ANODE MATERIAL FOR LITHIUM-ION BATTERIES

Samantha Bourrioux¹ – Yann Leconte¹ – Moulay Tahar Sougrati² – Lorenzo Stievano² – Laure Monconduit² – Zhichuan J. Xu³ – Madhavi Srinivasan³ – Alain Pasturel⁴

¹ CEA, IRAMIS, NIMBE, CNRS UMR 3685, F- 91191, GIF-SUR-YVETTE, France, e-mail : samantha.bourrioux@cea.fr

² Institut Charles Gerhardt-CNRS Université Montpellier II Place Eugène Bataillon, 34095 Montpellier, France

³ School of Materials Science and Engineering, Nanyang Technological University, SINGAPORE

⁴ SIMAP, UMR CNRS 5266, Grenoble INP, BP 75, 38402 SAINT-MARTIN D'HERES, FRANCE

Keywords: laser pyrolysis, zinc iron oxide, carbon coating, ZnFe2O4/C, composite, lithium-ion batteries

With the depletion of fossil fuels and the growing environmental concerns, lithium-ion batteries received considerable attention to contribute to the development of electric vehicles and storage for renewable energies. However, existing lithium-ion batteries cannot reach sufficient energy density to address the needs for such applications. One of the issues limiting the energy density is the low specific capacity of the graphite anode (372 mAh/g). Mixed-transition metal oxides with a spinel structure (AB₂O₄ – A, B transition metals) appear as a promising solution to replace graphite with a higher theoretical capacity (between 750 and 1000 mAh/g). Among various oxides, $ZnFe_2O_4$ is an interesting substitute for graphite, as an abundant, cheap, non-toxic and environmental-friendly material with a high theoretical capacity (1000 mAh/g). The nanostructuration of this material as well as a carbon coating around the particles can also help to maintain a mechanical stability during cycling and enhance the lithium kinetics.

 $ZnFe_2O_4/C$ nanoparticles presented in this work were synthesized by laser pyrolysis. In this vapor-phase process, a CO_2 laser is used to thermally decompose the precursors and synthesize nanoparticles. A solution containing $ZnCl_2$ and $FeCl_3.6H_2O$ dissolved in ethanol in a stoichiometric ratio was used for the synthesis of $ZnFe_2O_4/C$ nanoparticles. Ethylene was chosen as absorbent of the CO_2 laser to allow the precursors decomposition and air as the carrier gas. To vary the carbon content of the as-synthesized nanopowders, annealings under air atmosphere were realized (fig.1).




Figure 1. Particles morphology before annealing (left) and after annealing (right) Electrodes were then prepared using $ZnFe_2O_4/C$ (70% wt.), CMC (12% wt.) and carbon additives (VGCF 9% wt., carbon black 9% wt.) to be cycled vs. lithium metal and postmortem SEM was done to observe the electrodes morphology after cycling.