



**HAL**  
open science

# TiO<sub>2</sub>/graphene-based nanocomposites synthesized by laser pyrolysis: properties and application in perovskite solar cells

Raphaëlle Belchi, Aurélie Habert, Johann Bouclé, Nathalie Herlin-Boime

## ► To cite this version:

Raphaëlle Belchi, Aurélie Habert, Johann Bouclé, Nathalie Herlin-Boime. TiO<sub>2</sub>/graphene-based nanocomposites synthesized by laser pyrolysis: properties and application in perovskite solar cells. C’Nano 2017, Dec 2017, Lyon, France. cea-02341921

**HAL Id: cea-02341921**

**<https://cea.hal.science/cea-02341921>**

Submitted on 31 Oct 2019

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L’archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d’enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

## C'Nano 2017 - Call for proposals

### Poster and Oral presentations

#### Presentation (chose one)

Oral presentation

Poster presentation

#### Symposium - For a poster presentation, chose one or several symposiums according to your research topic

##### Workshop "NanoBio" - Life Nanoscience and NanoBiotechnology

- NanoBio 1 - NanoBioAssembly
- NanoBio 2 - Imaging and Nanoprobes
- NanoBio 3 - Biosensors

##### Workshop "Nanomaterial" - Innovative Nanomaterials and Advance Characterization

- Nanomat 1 :
- Nanomat 2
- Nanomat 3

##### Workshop "NanoInWorld" : Nanosciences for a Sustainable World

- NanoInWorld 1
- NanoInWorld 2 – Solar energy production and storage**
- NanoInWorld 3 – Nano integration in society

##### Workshop "NanoPhot" – Nanophotonics

- NanoPhot 1 - Resonance & quantum nano-optics
- NanoPhot 2 – Emergent nanomaterials for nanophotonics

**Title and affiliations (must fit in this box)**

**TiO<sub>2</sub>/graphene-based nanocomposites synthesized by laser pyrolysis: properties and application in perovskite solar cells**

**Raphaëlle Belchi<sup>1, 2</sup>, Aurélie Habert<sup>1</sup>, Johann Bouclé<sup>2</sup>, Nathalie Herlin-Boime<sup>1</sup>**

1. NIMBE, CEA, CNRS, Université Paris-Saclay, CEA Saclay 91191 Gif-sur-Yvette France

2. Univ. Limoges, CNRS, XLIM, UMR 7252, F-87000 Limoges, France

**Abstract (No longer than 250 words. Both the abstract and references must fit in this box. Style is Calibri 12, single line spacing)**

Since 2012, hybrid solar cells based on perovskite materials demonstrated several significant advances, with power conversion efficiencies now up to 22%, attracting strong interest within the scientific community [Zhou14, NREL efficiency table<sup>1</sup>]. Still, efforts remain to be performed to improve photo-current generation, especially concerning the development of efficient and reliable charge transporting electrodes and selective contacts. Titanium dioxide mesoporous layer, commonly used as electron transport layer, presents defects that trap electrons and favor electron-hole pair recombination. Carbon nanostructures are good electron transporters, therefore the use composites of TiO<sub>2</sub> and carbon nanostructures seems to be a relevant strategy to reduce recombination phenomena and thus to improve electron collection [Wang15].

Here, we combine specific know-hows on both perovskite solar cells processing and production of nano-scaled materials by laser pyrolysis. Our aim is to develop high quality TiO<sub>2</sub>/graphene nanocomposites with well-controlled physical properties for an optimal energy conversion.

Particular attention is paid to material characterizations such as morphological and structural analysis as well as physical properties evaluation of the nanocomposites and their role and effects within solar cells. Our results show a larger dark current in presence of graphene, as well as larger photocurrents and smaller series resistance, traducing the benefits of graphene for a better charge collection in the device. More generally, a significant increase in power conversion efficiency is observed for perovskite solar cells containing graphene in the TiO<sub>2</sub> mesoporous layer.

<sup>1</sup> [www.nrel.gov/ncpv/](http://www.nrel.gov/ncpv/)

[Zhou14] H. Zhou et al., Science 345 (2014) 542-546

[Wang15] J. Wang et al., ACS Applied Materials & Interfaces 7 (2015) 51-56