

Modelling approach to the evolution of physicochemical conditions in deep geological repository: alteration of engineered materials and redox control

Olivier Bildstein, P. Thouvenot, J. E. Lartigue, B. Cochepin, I. Munier

► To cite this version:

Olivier Bildstein, P. Thouvenot, J. E. Lartigue, B. Cochepin, I. Munier. Modelling approach to the evolution of physicochemical conditions in deep geological repository: alteration of engineered materials and redox control. Subsurface Environmental Simulation Benchmarking Workshop V, Oct 2016, La Corogne, Spain. cea-02438353

HAL Id: cea-02438353 https://cea.hal.science/cea-02438353

Submitted on 14 Jan 2020 $\,$

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

DE LA RECHERCHE À L'INDUSTRIE



MODELLING APPROACH TO THE EVOLUTION OF PHYSICOCHEMICAL CONDITIONS IN DEEP GEOLOGICAL REPOSITORY: ALTERATION OF ENGINEERED MATERIALS AND CLAYSTONES - REDOX CONTROL

O. Bildstein, P. Thouvenot, J.E. Lartigue

CEA (French Alternative Energies and Atomic Energy Commission)

B. Cochepin, I. Munier

Andra (French Radioactive Waste Management Agency)



SeS BENCH V – A CORUÑA - OCTOBER 13-15, 2016

www.cea.fr



Current design of deep underground repository for high and intermediate level long-lived waste



SeS BENCH V – A Coruña | OCT. 2016 | PAGE 2

Update of the atmospheric concrete carbonation benchmark



DESIGN: ILLW CELLS, SHAFTS (AND SEALS), ILLW DISPOSAL OVERPACK

Atmospheric carbonation of overpack during the operating period



SeS BENCH V - A Coruña | OCT. 2016 | PAGE 4

DE LA RECHERCHE À L'INDUSTRIE

DRYING AND CARBONATION PROCESSES OF ILLW OVERPACK



Coupling capability with
 « multiphase » flow and transport

GEOMETRY + BOUNDARY CONDITIONS

1D Cartesian – 5.5 cm divided in 11 cells (5 mm) for concrete 1 extra cell for "atmosphere"



Full multiphase codes :

Toughreact (CEA + T. Xu, JLU) iCORE (J. Samper, UDC) HYTEC ?? Drying with Richards' equation : MIN3P (S. Béa, CONICET ; U. Mayer, UBC) HYTEC (J. Corvisier, Mines Paristech) Crunchflow (CEA + C. Steefel, LBNL) DE LA RECHERCHE À L'INDUSTRI

COMPONENT 1: DRYING RESULTS



→ OK to use Richards' equation for benchmarking exercise

SeS BENCH V – A Coruña | OCT. 2016 | PAGE 7



COMPONENT 2: REACTION TRANSPORT RESULTS AT CONSTANT S_L

Making sure the same effective diffusion coefficient is used...

coupling equation (Millington-Quirk

relationship): $D_{eff} = D_0 \omega^a S_l^b$



For Crunchflow, b = 3.2 has to be used (instead of b = 4.2 for Toughreact)





COMPONENT 2B: CONCRETE CARBONATION AT CONSTANT \mathbf{S}_{L}



Carbonation front is similar, but the size of grid cells limits precise comparison



COMPONENT 2B: CONCRETE CARBONATION AT CONSTANT \mathbf{S}_{L}



Calcite precipitation front is similar (MIN3P a little ahead of time/distance)

SeS BENCH V - A Coruña | OCT. 2016 | PAGE 10

DE LA RECHERCHE A L'INDUSTRIE

COMPONENT 2B: CONCRETE CARBONATION AT CONSTANT S_L



Same mineral paragenesis but timing not exactly the same for all codes

cea

$\begin{array}{c} \textbf{COMPONENT 2B: CONCRETE CARBONATION AT} \\ \textbf{CONSTANT S}_{L} \end{array}$



Precipitation of gypsum in the simulation with Crunchflow and Hytec

SeS BENCH V - A Coruña | OCT. 2016 | PAGE 12



$\begin{array}{c} \textbf{COMPONENT 2B: CONCRETE CARBONATION AT} \\ \textbf{CONSTANT S}_{L} \end{array}$



Dawsonite does not precipitate with Crunchflow and Hytec Straetlingite more persistent with Crunchflow Ses BENCH DE LA RECHERCHE À L'INDUSTRIE

COMPONENT 2B: CONCRETE CARBONATION AT CONSTANT SL



Same mineral paragenesis but timing not exactly the same for all codes

Cesa

COMPONENT 2A: PORTLANDITE-CALCITE SYSTEM AT CONSTANT SL



cea

COMPONENT 2A: PORTLANDITE-CALCITE SYSTEM AT CONSTANT S_L



CONCRETE CARBONATION SUMMARY

✓ Concrete carbonation exercise

- differences between codes do not seem to be linked to the grid size or coupling method
- differences in results attributable to transport in the gas phase?
- ✓ CPU concerns: no SIA → small time steps → CPU times go up !
- Component 2a with simplified chemistry
- Component 3 with fully coupled drying+carbonation only with Toughreact

✓ New component : variable porosity?

Glass & steel corrosion and redox control in claystones DE LA RECHERCHE À L'INDUSTR

HLW DISPOSAL CELL



GEOMETRY AND TRANSPORT PROPERTIES

- 1D radial domain
- transport: diffusion only
- water saturated, constant porosity
- isothermal conditions
- H₂(g) from anoxic corrosion pH_{2(max)} = 60 bar

• glass

```
\Phi = 0.42 \text{ m}, \text{ H} = 1 \text{ m}
```

porosity = 0.12

• metallic components

total thickness = 0,095 m,

porosity = 0.25

connected fractured zone

0.4 * excavation diameter = 0.268 m

porosity = 0.20; $D_{eff}(25^{\circ}C) = 5.2 \ 10^{-11} \ m^2/s$

undisturbed claystone (50 m)
 porosity = 0.18; D_{eff}(25°C) = 2,6 10⁻¹¹ m²/s



Major challenge comes from:

- highly reactive system (strong pH and redox perturbation)
- complex geochemical system (15 chemical elements, 80 aqueous species, 60 minerals)

SeS BENCH IV – Cadarache | OCT. 2014 | PAGE 20

22 EXISTING BENCHMARK SUB-COMPONENTS

Component 1: iron corrosion only (45 000 yrs)

- magnetite, Ca-siderite, and greenalite dominate (oxide) (carbonate) (silicate)
 also smaller amounts of aluminosilicates
- (nontronites and saponites)
- POROSITY CLOGGING (not taken explicitly into account)
- modeling vs. experimental results iron/claystone at 90°C for 1 year
 small amount of magnetite
 siderite(-Ca), Fe-silicates

→ more phenomenological model for corrosion

Component 2: iron corrosion + glass alteration (100 000 yrs)



COMPONENT 1: RESULTS IN THE BASE CASE

ONLY 2 CODES : MIN3P-Crunchflow (a very good agreement is obtained!) ...



DE LA RECHERCHE À L'INDUSTR

CORROSION IN HLW DISPOSAL CELL





RELATED TOPICS

- production of hydrogen: how reactive is it?
- redox in claystones: who is in control?
- how is corrosion represented in reactive transport codes?
- reactivity of H₂ in claystones
 (in tiny 20 nm connected pores)
 - \rightarrow only at interfaces in repository
 - \rightarrow redox control in claystones?
 - \rightarrow RN sorption/migration?
 - \rightarrow porosity clogging



discussion: coupling of electrochemical corrosion reactions with reactive transport codes

✓ Corrosion in reactive transport codes

```
changes in pH and Eh occur through:
```

$$Fe(s) + 2 H_2O \rightarrow Fe^{2+} + H_2 + 2 OH^{-}$$



... but the paragenesis of secondary minerals is not predicted correctly

To match the mineralogical paragenesis, we have to modify:

- (very low) diffusional properties in the corroded layer
- (high) magnetite precipitation rate



Corrosion: an electrochemical model

 \checkmark redox reactions occurring at the interface 1

- non-equilibrium reactions involving electrons in the conduction band
- ✓ corrosion generates fluxes
 of Fe²⁺, Fe³⁺, H₂, H⁺, ...



Diffusion Poisson Coupled Model (DPCM) from Bataillon et al. *Electrochem. Acta* 2010



Coupling of electrochemical corrosion reactions with reactive transport codes:

- \checkmark use elemental fluxes (Fe, H₂)?
- use mineral reaction rates (corrosion and oxide layer precipitation/dissolution)?
- \checkmark use fluxes for Fe²⁺ and Fe³⁺ and aqueous kinetics?

THANK YOU FOR YOUR ATTENTION

Commissariat à l'énergie atomique et aux énergies alternatives Centre de Cadarache | 13108 Saint Paul-lez-Durance T. +33 (0)4 42 25 37 24 | F. +33 (0)4 42 25 62 72

Etablissement public à caractère industriel et commercial RCS Paris B 775 685 019

Direction de l'Energie Nucléaire Département des Technologies Nucléaires Service de Modélisation des Transferts et de Mesures Nucléaires

Update on glass/iron/clay benchmark DE LA RECHERCHE À L'INDUSTRI

RESULTS IN THE BASE CASE (3)













DE LA RECHERCHE À L'INDUSTRI

RESULTS IN THE BASE CASE (4)











in the clay zone

	D aphnite_14A - crunchflow F e-S aponite-N a - crunchflow
	G reenalite - crunchtiow
	Pyrrhotite-alpha - crunchflow
	Daphnite 14 A - MIN 3P
- -	G reenalite - MIN 3P
_	F - C H - H - MINAD

Fe-Saponite-Na - MIN3P Pyrrhotite-alpha - MIN3P

