



## Mixing in rivers under complex conditions

L Gond, E Mignot, J Le Coz, L Kateb

### ► To cite this version:

L Gond, E Mignot, J Le Coz, L Kateb. Mixing in rivers under complex conditions. Journée du GIS HED2 (Groupement d'Intérêt Scientifique “ Hydraulique pour l'Environnement et le Développement Durable ”), Société Hydrotechnique de France (SHF) / GIS-HED, Nov 2019, Marne la vallée, France. cea-02972469

HAL Id: cea-02972469

<https://cea.hal.science/cea-02972469>

Submitted on 20 Oct 2020

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



# Mixing in rivers under complex conditions

L. Gond<sup>123</sup>, E. Mignot<sup>1</sup>, J. Le Coz<sup>2</sup>, L. Kateb<sup>3</sup>

<sup>1</sup> LMFA - INSA Lyon, France

<sup>2</sup> Irstea, Lyon, France

<sup>3</sup> CEA, Cadarache, France

# Mixing in rivers under complex conditions


1/ Goal

2/ Theoretical aspects


3/ Field procedure and application



# 1. Goal



Evaluate the variability of the transverse mixing coefficient in inhomogenous rivers



## 2. Theoretical aspects



Simulation of a pollutant release in river



# Advection-diffusion in turbulent regime

$$\frac{\partial c}{\partial t} + \bar{u}_i \frac{\partial c}{\partial x_i} = D \frac{\partial^2 c}{\partial x_i^2} + \frac{\partial(\varepsilon_{ti} \frac{\partial c}{\partial x_i})}{\partial x_i}$$

- $D$  = molecular diffusivity
- $\varepsilon_{ti}$  = turbulent diffusivity
- $\bar{u}_i$  = Time-averaged velocity vector
- $c$  = Concentration
- overbar = time-averaged
- $x$  = space,  $t$  = time,  $i = 1, 2, 3$

Scalar dispersion in rivers is governed by:


- 1/ molecular diffusion
- 2/ turbulent diffusion
- 3/ advection by secondary currents + recirculation zones



# Simplification for a 1D flow

Hypotheses =

- \* Turbulent regime  $\rightarrow D \ll \varepsilon_t$
- \* Uniform 1D horizontal flow  $\rightarrow$  depth averaging:  $\bar{U}_x = u_d(z)$  and  $U_z = U_y = 0$
- \* Vertical mixing  $\gg$  transverse mixing  $\rightarrow$  vertical dispersion neglected
- \* Considering the averaged transverse mixing coefficient  $E_z$



*Streamtube model equation*

$$\frac{1}{u_d} \frac{\partial c_d}{\partial t} + \frac{\partial c_d}{\partial x} = \frac{\partial}{\partial q} (\varepsilon_z u_d h^2 \frac{\partial c_d}{\partial q})$$

*Constant coefficient equation*

$$\frac{1}{u_d} \frac{\partial c_d}{\partial t} + \frac{\partial c_d}{\partial x} \approx E_z \psi U H^2 \frac{\partial^2 \bar{c}_d}{\partial q^2}$$

Yotsukura & Cobb (1972)

->  $u_d$  = local streamwise velocity –  $h$  = local depth

->  $c_d$  = depth average concentration

->  $z$  = transverse position

->  $\varepsilon_z$  = transverse mixing coefficient

$q = \int_0^z u_d(\delta) h(\delta) d\delta$  = cumulative discharge

->  $E_z$  = averaged transverse mixing coefficient

$$\psi U H^2 = \frac{1}{Q} \int_0^Q u_d(q) h(q)^2 dq$$

# Instantaneous injection at $q=q_0$

Time-dependent equation :  $c_d(x, q, t = 0) = c_d(x, q, t = +\infty) = 0$

$$\int dt \frac{1}{u_d} \frac{\partial c_d}{\partial t} + \frac{\partial c_d}{\partial x} \approx E_z \psi U H^2 \frac{\partial^2 \bar{c}_d}{\partial q^2}$$

$$\frac{\partial \theta}{\partial x} = E_z \psi U H^2 \frac{\partial^2 \theta}{\partial q^2}$$


Local dosage :

$$\theta(x, q) = \int_0^\infty C(x, q, t) dt$$

General solution :


$$\theta_u(x, q) = \frac{M}{\sqrt{4\pi E_z \psi U H^2 x}} \exp \left[ -\frac{q^2}{4E_z \psi U H^2 x} \right]$$

Solution with mirror :  $\theta(x, y) = \theta_u(x, q + q_0) + \theta_u(x, q - q_0) + \sum_{n=1}^N \theta_u(x, 2nQ \pm q \pm q_0) + \theta_u(x, 2nQ \pm q \mp q_0)$



(Seo & al. (2016))

$E_z = \text{best fit}$




(Beltaos, 1980)

### 3.1 Field procedure : Application to the Drac River

#### Drac River, France



Les grands bassins fluviaux de France



## Step 1 : Determine segments to study

Segments studied must :

- Have an easy access
- Have a homogenous geometry (roughness, width, depth, slope)
- Be long enough (too short -> no mixing measurable)
- Not too far from injection (-> complete mixing)



## Step 2 : Calibrate probes

Fluorescence probes :


- probes = Albillia GGNU-FL30 series 500 & 900 \*6
- probes = TQ-tracer \*2



Calibration with several controlled Rhodamine concentration

+ Temperature corrections

(EDF)




Albillia




TQ-tracer

## Step 3 : Measure bathymetry + velocity field at each survey cross sections

ADCP (Acoustic Doppler Current Profiler)




ADCP installed on a River-Drone



ADCP system (from Muller & Wagner, 2013)

## Step 4 : Install sensors along 2 cross sections (near-bed)




Example of line of TQ-Tracer probes (EDF)




*Survey cross-sections*





## Step 5 : Sudden Rhodamine injection upstream




## Step 6 : Measure $C(t)$ on each probe, evaluate $\theta$ , $\theta=f(q)$



Using  
Calibration +  
temperature  
correction






Aggregate  
all data



## Step 7 : Fit analytical model & estimate $E_z$


$$\frac{\partial \theta}{\partial x} = E_z \psi U H^2 \frac{\partial^2 \theta}{\partial q^2}$$



From injection to S1 :  $E_{z1} = 0.11 \text{ m}^2/\text{s}$   
 From S1 to S2:  $E_{z2} = 0.35 \text{ m}^2/\text{s}$

Impervious emerging bloc strongly increase  
 the transverse mixing coefficient


# Comparison of $E_{z1}$ with literature data



↓

$$\frac{E_{z1}}{Hu *}=0.8$$

$B/H$  = channel aspect ratio  
 $\lambda$  = Darcy friction coefficient



### 3.2 Application to the Durance river



## Les grands bassins fluviaux de France



18 transverse sections, 4 injection points :



Many different bed conditions on a small area :



Shallow waters with rocks



Boulders



Channel with boulders

Analysis still in progress !



Deep and slow waters




Perspectives :

- Reproduce hydraulic conditions in laboratory (LMFA – INSA Lyon)




Study of different flows with rough beds



Effect of roughness height on the mixing coefficient

- Presentation of the results at RiverFlow 2020



Scientific paper

# References

Beltaos, S. (1980), Transverse mixing tests in natural streams. *Journal of the Hydraulics Division*, 106(10), 1607-1625.

Fischer, H.B, List, J.E., Koh, C.R., Imberger, J. (1979), Mixing in inland and coastal waters, Elsevier, New York

Gaultieri, C., Mucherino, C. (2007), Transverse turbulent diffusion in straight rectangular channels. *5<sup>th</sup> international symposium on environmental hydraulics (ISEH 2007), Tempe, USA*.

Rutherford, J.C. (1994), River mixing, Wiley, Chichester, U.K.

Yotsukura, N., Cobb, E. D., 1972. Transverse diffusion of solutes in natural streams. *Geological Survey Professional Paper* 582-C.

Il Won Seo, A.M.ASCE, Hwang Jeong Choi, Young Do Kim, and Eun Jin Han (2016), Analysis of Two-Dimensional Mixing in Natural Streams Based on Transient Tracer Tests