

Smart grids and photovoltaics: perspectives of photovoltaics on the power exchange

Bruno Robisson, Alexandre Mignonac

▶ To cite this version:

Bruno Robisson, Alexandre Mignonac. Smart grids and photovoltaics: perspectives of photovoltaics on the power exchange. Introducing massive amount of photovoltaic and wind energies in the electric grids, MCAST, May 2019, Saint-Paul Lez Durance, France. cea-03211004

HAL Id: cea-03211004 https://cea.hal.science/cea-03211004

Submitted on 28 Apr 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

FROM RESEARCH TO INDUSTRY



www.cea.fr

SMART GRIDS AND PHOTOVOLTAICS: PERSPECTIVES OF PHOTOVOLTAICS ON THE POWER EXCHANGE

Workshop Jump2Excel

Introducing massive amount of photovoltaic and wind energies in the electric grids

21 MAY 2019 BRUNO ROBISSON – ALEXANDRE MIGNONAC






Panorama of the electrical system

Generators characteristics and associated "products"

Using these "products" to balance the system


Opportunities of PV plants in markets



• **SECURITY OF SUPPLY** : better coordinate the EU's supply of and demand for energy



The electricity supply must be equal to the electricity demand at all times (i.e. on a second-by-second basis), otherwise the system risks to break down



BUT neither party can meet its contractual obligations with perfect accuracy.

Due to


- Forecast production or consumption errors
- Unpredictable problems


 \rightarrow gaps between load and generation.

PANORAMA: BALANCING MARKET



A balancing market has been set up to bridge this gap quickly and precisely.






GENERATORS CHARACTERISTICS



Electricity Generators produce **electricity** \rightarrow **direct valorization through energy market**



Type of fuel : renewable versus non-renewables resources

 $\rightarrow\,$ direct valorization of renewable energy through guarantees of origin (not described in this presentation)

CO₂ emissions: Low-carbon energy sources versus fossil fuels.


 \rightarrow indirect valorization through carbon price (not described in this presentation)



Generation capacity : the maximum power they generators can produce.

Capacity (law) :

Each supplier is required to obtain sufficient capacity guarantees to cover the consumption of all of their customers during periods of peak national demand.




 \rightarrow direct valorization through the capacity market

GENERATOR: FLEXIBILITY



Flexibility :

« The generator is committed to increase (resp. decrease) from SetPoint its power production up to *UPWARD* MW (resp. downto *DOWNWARD* MW) during at most X minutes ("*hold time"*) if a command order is sent Y minutes in advance ("*Full Activation Time –FAT"*)»





Valorization depends of the Full Activation Time (FAT):

- FAT>= ~ 1h = « slow-flexibility » \rightarrow implicit valorization in the energy market
- FAT < \sim 1h = « fast-flexibility » \rightarrow explicit valorization in the balancing service market

Different « reserve/balancing » products:

- Frequency Containment Reserve (FCR): FAT ~ 10 s, Hold Time = few minutes
- automatic Frequency Restoration Reserve (aFRR): FAT ~ 5-6 min , Hold Time = few minutes
- manual Frequency Restoration Reserve (mFRR): FAT ~ 13-15min , Hold Time = few hours
- Recovery Reserve (RR): FAT ~ 30min , Hold Time = few hours


Balancing Service Provider (BSP) in the European Union Internal Electricity Market is a market participant providing Balancing Services to its Connecting TSO.




Cea BALANCING ENERGY



Balancing energy : energy used by Transmission System Operators (TSOs) to perform balancing and provided by the Balancing Service Provider (BSP).



Balancing capacity : a *volume of capacity* that a Balancing Service Provider (BSP) has agreed to hold to the transmission system operator for the duration of the contract. The BSP has also agreed to submit bids for a corresponding volume of balancing energy.




Cea BALANCING CAPACITY



Cea system balancing: example



- S1 is a supplier who owns 2 generators (G1 a biomass plant and G2 a solar plant) and who supplies consumers
- S1 is a Balance Responsible Party (BRP)
- S1 is a Balancing Service Provider (BSP)
- S2 is a supplier who owns generators and who supplies consumers and BRP
- The generators and consumers are connected through the public grid




Consumers of S2 P 13

Cea PLANNING PHASE (S1): ENERGY PROVIDING



From several months in advance to 15h@21/05/2019

- S1, as supplier, estimates the sum of the power consumption of his consumers at 16h-17h the 21/05/2019
- S1, as generators owner, estimates the energy which may be produced by his generators.
- S1, as BRP, purchases/sells energy from/to another supplier/utility owner to set 'energy imbalance' as close as possible to zero (« Self dispatch »).




PLANNING PHASE (TSO): BALANCING ENERGY CQAAND CAPACITY PROVIDING



From several months in advance to 15h@21/05/2019

- TSO estimates the need of balancing capacity (resp. energy) for the whole network
- TSO purchases this amount of capacity (resp. energy) to. BSP (here S1) •




EXAMPLE OF PLANNING PHASE





Planning phase for delivery of 16h-17h@21/05/2019












EXECUTION PHASE : CASE 'UP'



Execution phase of 16h-17h@21/05/2019 i.e. during 15h-17h@21/05/2019




Supplier S2 as balance responsible

EXECUTION PHASE : CASE 'UP'




Execution phase of 16h-17h@21/05/2019 i.e. during 15h-17h@21/05/2019



SETTLEMENT PHASE : CASE 'UP'







EXECUTION PHASE: CASE 'DOWN'





Execution time of 16h-17h@21/05/2019


i.e. during 15h-17h@21/05/2019















Producer's revenues depend, among others, on the price of capacity, of energy, of balancing capacities, of balancing energy and of the sale of guarantees of origin.

Capacity markets :

• Low potential revenues because the peak load is not in phase with solar production

Energy Markets :

- Revenues of Solar energy : market price + capacity + "complement of remuneration"
- Downward regulation activated by the energy supplier could be cost-effective, for example, in case of negative prices on spot markets (case [A])
- Need of reliable production forecast to reduce Energy Imbalance (of BRP)

Balancing Markets :

- Downward reserve : cost-effective if Downward Balancing Capacity incomes is greater than Balancing Energy charges
- Upward reserve: a priori not interesting because the voluntary decrease of production to deliver upward Balancing Capacity is very costly (except in case [A])
- Need of reliable production forecast to reduce Balancing Energy Imbalance and to maximize Balancing Capacity (of BSP)





Very difficult (even impossible?) to forecast the energy producer's revenues in the long term. But, the relative value of the balancing energy compared to the value of the energy could increase with the increase of renewables in the production mixt.

Capacity markets :

• Revenues could increase if the peak load becomes in phase with the solar production (due to air-conditionning or big changes in power consumption habits)

Energy Markets :

Revenues of Solar energy: market price + capacity + "complement of remuneration"

Balancing Markets :

 Very low response time of PV systems could be valorized for balancing mecanism in the future (for example in fast frequency response, i.e. FAT ~ 2s)