



Impact of the aspect ratio on tokamak reactor design

Yanick Sarazin

► To cite this version:

| Yanick Sarazin. Impact of the aspect ratio on tokamak reactor design. IAEA FEC 2021 - The 28th IAEA Fusion Energy Conference, May 2021, Nice (Virtual Conference), France. cea-03253683

HAL Id: cea-03253683

<https://cea.hal.science/cea-03253683>

Submitted on 8 Jun 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Impact of the aspect ratio on tokamak reactor design

Y. Sarazin, J.-L. Duchateau, X. Garbet , Ph. Ghendrih, R. Guirlet, J. Hillairet, B. Pégourié, A. Torre and R. Varennes

CEA, IRFM, F-13108 St-Paul-Lez-Durance, France

yanick.sarazin@cea.fr




Context - motivations



Tokamak design relies on the use of **empirical scaling laws** for the energy confinement time τ_E [e.g. Zohm, NF 2013]

These scaling laws exhibit **large variances** (~30%) and **different scaling regarding critical parameters** (e.g. aspect ratio $A=R/a$)




What impact on Tokamak design ?

What consequences for ITER & DEMO [Coleman, FED 2016] ?

Commissariat à l'énergie atomique et aux énergies alternatives Y. Sarazin 9 avril 2021 2

Constitutive relations: P_{fus}



Commissariat à l'énergie atomique et aux énergies alternatives Y. Sarazin 9 avril 2021 4

Constitutive relations: $Q \dots$ hence τ_E

n and T constrained by plasma physics

Soft limits in (n,T) set by plasma MHD (& turbulence?) instabilities

$$\begin{aligned} Q &\doteq \frac{P_{fus}}{P_{add}} & P_{fus} &= P_\alpha + P_n = \lambda P_\alpha & \lambda \approx 4.94 \\ P_{net} &\doteq P_\alpha + P_\Omega + P_{add} - P_{rad} & P_{net} &= \gamma_{rad}(P_\alpha + P_{add}) \\ \Rightarrow P_{net} &= \gamma_{rad} P_{fus} \frac{1 + Q/\lambda}{Q} & \text{Simplification: } P_{rad} &= (1 - \gamma_{rad})(P_\alpha + P_{add}) \\ &0 \leq \gamma_{rad} \leq 1 \end{aligned}$$

Link with $\tau_E \rightarrow$ triple product

$$\begin{aligned} \tau_E &= \frac{3nT\mathcal{V}}{P_{loss} - P_{rad}} \sim \frac{nTR^3}{P_{net}} \\ \Rightarrow nT\tau_E &\sim \frac{Q}{1 + Q/\lambda} \end{aligned}$$

Empirical Scaling Law $\tau_E = F(n, I_p, R, B, P_{net}, \dots)$


Commissariat à l'énergie atomique et aux énergies alternatives Y. Sarazin 9 avril 2021 5

Commissariat à l'énergie atomique et aux énergies alternatives Y. Sarazin 9 avril 2021 6

Commissariat à l'énergie atomique et aux énergies alternatives Y. Sarazin 9 avril 2021 7

Finding suitable (R,B) solutions - ITER

ITER target: $P_{fus}=500$ MW, $Q=10$
4 unknowns (R, B, f_G, β_N), 2 equations
 \Rightarrow some freedom (here, $f_G=0.85$)



Additional constraints:
- Power flux on target plates
- Magnets → "Radial Built"
- Duration of inductive plateau current [Duchateau, FED 2014]

Using IPB98(y,2) scaling law
 \rightarrow ITER specifications are recovered [ITER Physics basis, NF 1999]

Using DS03 scaling law [Petty PoP 2004, Sips NF 2018]
 \rightarrow lower B , higher β_N

Possible issue: disruption threats

Commissariat à l'énergie atomique et aux énergies alternatives Y. Sarazin 9 avril 2021 8

DEMO should operate at large β_N if DS03 holds

EU-DEMO target: $P_{fus}=2.037$ GW, $Q=40$ [Wenninger, NF 2017]

Typical parameters are recovered with IPB98(y,2) scaling law:
 $R \sim 9.1$ m $B \sim 5.6$ T $\beta_N \sim 2.2$

Much larger β_N with DS03 scaling law:
 $R \sim 9.1$ m $B \sim 4.2$ T $\beta_N \sim 3.8$

Challenging in a reactor which aims at 0 disruption

Much larger B with ITPA20 scaling law:
 $R \sim 9.1$ m $B \sim 7.0$ T $\beta_N \sim 1.4$

[Verdoollaeghe NF 2021]

Commissariat à l'énergie atomique et aux énergies alternatives Y. Sarazin 9 avril 2021 9

What aspect ratio for DEMO ? A scan @ $R=Cst$

What aspect ratio for DEMO ? A scan $\beta_N @ =Cst$

Conclusions

Aspect ratio $A=R/a$
- Central design parameter (plasma stability, disruption forces, tritium breeding, maintenance, cost, ...)
- Some freedom in its choice

Opposite scalings of τ_E

IPB98(y,2): $\omega_c \tau_E \sim A^{-0.73}$

DS03: $\omega_c \tau_E \sim A^{+1.30}$


ITPA20: $\omega_c \tau_E \sim A^{+1.70}$

Favorable scaling of $\omega_c \tau_E$ does NOT guarantee the advantage of working at large A

Assuming prescribed $R=9.1$ m

- B increases with A


- Cost \sim Volume $\times B^2$ increases with A



Assuming prescribed β_N :

- Opposite trends for R , B , Volume and "Cost"

\Rightarrow No clear conclusion



Development of the simple and comprehensive 0D model SCALA for tokamak design (DEMO) + performance evaluation (ITER)

ITER and DEMO characteristics are recovered when using IPB98(y,2) scaling law → robustness of the approach

To achieve the same performance (Q, P_{fus}):

- DS03 scaling law requires to operate at larger β_N

- ITPA20 scaling law requires to operate at larger B

Increase of $\omega_c \tau_E$ with aspect ratio $A=R/a$ DOES NOT automatically imply that large A tokamaks should be favored

Scaling laws leave unclear the benefit of large/small A
 \rightarrow consolidate scaling laws with $A \neq 3$ (e.g. WEST data A~5)