



HAL
open science

High quality crystalline boron doped diamond growth on spherical monodisperse silica particles and impact of seeding density on the microstructure

K Henni, I Stenger, J-S Merot, F Fossard, Jean-Charles Arnault, H Girard

► To cite this version:

K Henni, I Stenger, J-S Merot, F Fossard, Jean-Charles Arnault, et al.. High quality crystalline boron doped diamond growth on spherical monodisperse silica particles and impact of seeding density on the microstructure. MRS Spring Meeting, May 2022, Online, France. . cea-03681020

HAL Id: cea-03681020

<https://cea.hal.science/cea-03681020>

Submitted on 30 May 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

High quality crystalline boron doped diamond growth on spherical monodisperse silica particles and impact of seeding density on the microstructure

K.Henni¹, I. Stenger², J-S. Merot³, F. Fossard³, J. C. Arnault¹ and H. A. Girard¹

¹Université Paris-Saclay, CEA, CNRS, NIMBE, CEDEX, 91 191 Gif sur Yvette, France

² Université Paris-Saclay, UVSQ, CNRS, GEMaC, 78000 Versailles, France

³Université Paris-Saclay, ONERA-CNRS, Laboratoire d'Etude des Microstructures, BP 72, 92322, Châtillon, France

CO₂ conversion to chemical fuels such as alcohol and hydrocarbons has been found to be one of the most promising renewable energy source. It has urged the scientific community to develop efficient material in favor of CO₂ reduction. Boron-doped diamond (BDD) electrodes have aroused an interest among scientists for its outstanding electrochemical properties in particular its wide potential window, making it a good candidate for the electrochemical reduction of CO₂ [1]. Moreover, hydrogenated BDD films, under UV illumination, could generate solvated electrons in aqueous solutions, making it highly relevant for photo(electro)catalytic CO₂ reduction [2].

In this study, we report an innovative approach that aims to grow a BDD coating onto monodisperse silica cores to obtain SiO₂@BDD core-shell particles by microwave plasma chemical vapor deposition (MPCVD). After removal of the core, hollow BDD could be used in the development of new electrode architectures which allows a significant gain in electro/photo-active surface. Currently, BDD particles are obtained by grinding massive BDD films, expensive process that produces in small amounts highly polydisperse particles.

Several investigations have correlated the electrochemical behavior of BDD with its crystallinity [3]. We therefore dedicated our work on the influence of several parameters on the crystalline quality, the morphology and the sp²/sp³ carbon ratio of diamond coating. These parameters are (i) the methane concentration in the gas phase, (ii) the nature of seeds (milled or detonation nanodiamonds), (iii) their density and (iv) the oxygen species removed from seeded silica cores during MPCVD process. The morphology of diamond coatings was characterized by scanning electron microscopy (SEM). Results showed that the lower initial seeds density and methane concentration, the larger grain size we obtain with faceted structure. Raman measurements on diamond coatings allowed to compare diamond crystalline quality and sp²/sp³ carbon ratio for the different growth conditions. Transmission electron microscopy (TEM), coupled with EELS, EDS spectroscopies were performed in order to access the diamond microstructure. The associated growth mode and the nature of the SiO₂ / diamond interface were studied in cross-sections obtained by Focused ion beam (FIB).

[1] Natsui et al. (2018), *Angewandte Chemie*, 130, 2669

[2] Zhang et al. (2014), *Angewandte Chemie*, 126, 9904

[3] Garcia-Segura et al. (2015), *Electrochemistry Communications*, 59, 52

