

Biomass-based hard carbon as negative electrode for sodium-ion batteries

Julie Michel, Maria José Rivas Arrieta, Capucine Dupont, Loic Simonin, Eleanora Borén, Maria Kennedy

► To cite this version:

Julie Michel, Maria José Rivas Arrieta, Capucine Dupont, Loic Simonin, Eleanora Borén, et al.. Biomass-based hard carbon as negative electrode for sodium-ion batteries. HTC 2023 - 3rd International Symposium on Hydrothermal Carbonization, May 2023, Séoul, South Korea. cea-04160818

HAL Id: cea-04160818 https://cea.hal.science/cea-04160818

Submitted on 12 Jul2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés. May 18-21, 2022

Seoul, Korea

Preferred type of presentation:	
(Please choose only one)	POSTER
Preferred track:	□ Fundamentals
(Please choose only one)	⊠ Applications
	□ Upscaling/Commercialization
$oxed{B}$ I am interested in publishing my paper in a special issue of a peer-reviewed journal.	
(Journal name will be announced later)	

Biomass-based hard carbon as negative electrode for sodium-ion batteries

J. Michel^{1,2*}, M. Rivas Arrieta¹, C. Dupont¹, L. Simonin², E. Boren³, M. Kennedy¹
1 IHE Delft, Delft, Netherlands
2 CEA/LITEN/DEHT, Université Grenoble Alpes, Grenoble, France
3 Department of Chemistry, Umeå University, 90187 Umeå, Sweden
*e-mail: julie.michel@cea.fr

Abstract

Sodium-ion batteries are a promising technology to respond to the critical availability of lithium. The most suitable material for negative electrode is hard-carbon, which can be obtained from biomass. Usually, it is synthetized by two pyrolysis steps at low (about 450° C) and high temperature (1500° C), which requires a dry starting material. Unlike pyrolysis, hydrothermal carbonization (HTC) has the advantage of immerging the material in water: there is no need in drying the biomass before processing. Furthermore, during the process, inorganics tend to leach in the liquid phase, which is can be positive for the resulting electrochemical properties of hard-carbon. It makes HTC an interesting alternative to the first low temperature pyrolysis. The objective of this work is to understand the influence of initial feedstock composition, both on the material properties after HTC and the high-temperature pyrolysis and on the final battery performances in order to optimize the chain feedstock/process/product. Elemental compositions were characterized at the different steps by CHNS analysis, ICP-OES and UV-visible spectroscopy, and crystalline structure was characterized by XRD. As expected, the inorganic elements leached to a large extent to the liquid phase during HTC, however in different proportions depending on the feedstock tested. The resulting hard carbons contained therefore little impurities and showed very good performances when tested in batteries, both in terms of initial columbic efficiency, cyclability among 100 cycles and specific capacity. These performances are promising since they are similar to graphite in lithium-ion batteries.

Keywords: biomass-based hard carbon, energy storage, sodium-ion battery, inorganic elements