1 2	Supplementary Information for the Manuscript:
3	Time-resolved laser-induced fluorescence spectroscopy and chemometrics for
4	fast identification of U(VI)-bearing minerals in a mining context
5	Jean-Baptiste Sirven <sup>a,*</sup> , Stéphanie Szenknect <sup>b</sup> , Evelyne Vors <sup>a</sup> , Eddie Anzalone <sup>b</sup> , Sofian
6	Benarib <sup>b</sup> , Papa-Masserigne Sarr <sup>a</sup> , Pascal E. Reiller <sup>a</sup> , Adel Mesbah <sup>c</sup> , Nicolas Dacheux <sup>b</sup> , Thomas
7	Vercouter <sup>a,1</sup> , Michaël Descostes <sup>d,e</sup>
8	<sup>a</sup> Université Paris-Saclay, CEA, Service d'Etudes Analytiques et de Réactivité des Surfaces (SEARS), F-
9 10	91191 Gif-sur-Yvette, France. <sup>b</sup> ICSM, Univ Montpellier, CEA, CNRS, ENSCM, Site de Marcoule, Bagnols-sur-Cèze, France.
10	<sup>c</sup> IRCELYON, CNRS – UCBL, 2 avenue Albert Einstein, 69626 Villeurbanne Cedex, France.
12	<sup>d</sup> ORANO Mining, Environmental R&D Dpt., 125 avenue de Paris, 92320 Chatillon, France.
13	<sup>e</sup> Centre de Géosciences, MINES Paris, PSL Research University, Paris, France.
14 15	<sup>1</sup> present address: Université Paris-Saclay, CEA, Service d'Etudes des Matériaux Irradiés (SEMI), F-
16	91191 Gif-sur-Yvette, France
17	* Corresponding author: jean-baptiste.sirven@cea.fr
18	
19	This Supplementary Information describes the preparation and characterization of the
20	synthetic samples, and gives the prediction results of models 1 and 2 for the training set.
21	Please note that the TRLF spectra of all samples are available upon request.
22	Content
23	S.1. Preparation of synthetic uranyl phases2
24	S.1.1. Uranium oxides and oxide-hydroxy-hydrates2
25	S.1.2. Uranium vanadate2
26	S.1.3. Uranium phosphates2
27	S.1.4. Uranium sulfates3
28	S.1.5. Uranium silicates
29	S.1.6. Uranium carbonates4
30	S.1.7. Adsorption of uranyl on clays5
31	S.2. Characterisations of the synthetic samples6
32	S.3. Prediction results on the training set13
33	<b>S.4. References</b>

## 34 S.1. Preparation of synthetic uranyl phases

35 The uranyl nitrate hexahydrate salt used in these syntheses was purchased from Sigma-Aldrich, and

36 the uranyl acetate dehydrate and uranyl sulfate from Prolabo. The solutions were prepared with

- 37 deionised water (18.2 M $\Omega$  cm, MilliQ gradient system, Millipore) and analytical grade reagents were
- 38 purchased from Sigma Aldrich, Fisher Scientific, Fluka and VWR.

## 39 S.1.1. Uranium oxides and oxide-hydroxy-hydrates

- 40 The UO<sub>3</sub> powder (sample ICSM21-04) was obtained by the thermal conversion of a sample of studtite, 41 UO<sub>2</sub>(O<sub>2</sub>)·4H<sub>2</sub>O at 450°C in air [S1]. Synthetic metaschoepite, UO<sub>3</sub>·2H<sub>2</sub>O (sample EA21-008) was obtained 42 by the hydration of amorphous  $UO_3$  powder in steam for 1 h. 0.5 g of  $UO_3$  powder was spread in an 43 alumina crucible above a vessel containing 1 L of boiling deionised water. The complete apparatus was 44 covered with aluminium foil and the sample was exposed to steam for 1 hour. The colour of the sample 45 turned progressively to yellow. The same protocol was used to prepare the UO<sub>3</sub>·0.8H<sub>2</sub>O (sample EA21-46 016) except that the steam exposure lasted 3 h. Then the samples were stored at room temperature 47 in air. The hydration rate of the samples was determined by thermogravimetric analysis (TGA, Setaram 48 Setsys Evolution). About 30 mg of powder was heated in air at a rate of 5°C.min<sup>-1,</sup> from room 49 temperature to 800°C, in order to follow the dehydration step and then the transition from UO<sub>3</sub> to 50 U₃O<sub>8</sub>.
- 51 Synthetic billetite,  $Ba(UO_2)_6O_4(OH)_6 \cdot nH_2O$  (sample EA21-049); becquerelite,  $Ca(UO_2)_6O_4(OH)_6 \cdot nH_2O$ 52 (samples EA21-048 and EA21-055) and compreignacite, K<sub>2</sub>(UO<sub>2</sub>)<sub>6</sub>O<sub>4</sub>(OH)<sub>6</sub>·nH<sub>2</sub>O (sample EA21-050) 53 were prepared following the protocol proposed by Vochten and Van Haverbeke [S2]. 0.1 g of 54 metaschoepite was placed in a PFA reactor (Savillex<sup>®</sup>) with respectively 200 mL of 5.10<sup>-3</sup> mol/L BaCl<sub>2</sub>, 55 5.10<sup>-3</sup> mol/L CaCl<sub>2</sub> or 10<sup>-2</sup> mol/L KCl aqueous solution. The reactors were closed and placed in an oven 56 at 60°C for 7 days. Then, the remaining solid was filtered, and washed three times with deionised water 57 and once with ethanol by centrifugation in 40 mL of solvent. The samples were then dried for 24 h at 58 60°C.

## 59 **S.1.2. Uranium vanadate**

60 Carnotite,  $K_2(UO_2)_2(VO_4)_2 \cdot 3H_2O$  (sample ICSM15-03) was prepared using a dry chemistry process 61 [S3][S4].  $K_2CO_3 UO_3$  and  $V_2O_5$  precursors were first dried for 24 h at 90°C. Then, the reactants were 62 mixed in stoichiometric proportion and three successive cycles of ball milling (30 min at 30 Hz) and 63 calcination at 600°C for 24 h in air of the mixture were made to obtain the final sample.

## 64 S.1.3. Uranium phosphates

- Synthetic chernikovite,  $(H_3O)_2(UO_2)_2(PO_4)_2 \cdot 6H_2O$  (sample ICSM15-04) was prepared by direct precipitation following the protocol initially proposed by Vochten and Deliens [S4][S5][S6]. For the synthesis of about 1 g of chernikovite, a 2 mol/L phosphoric acid solution was added to a 1.46 mol/L uranyl nitrate solution (in 5  $10^{-3}$  HNO<sub>3</sub>) in order to obtain an excess of 10 mol. % of phosphates in the mixture. The resulting solution was stirred at room temperature for 1 h then aged for 3 days, following which the precipitate was recovered by filtration, washed three times with deionised water and once with ethanol by centrifugation in 40 mL of solvent. The samples were then dried for 24 h at 40°C.
- 72 Synthetic autunite, Ca(UO<sub>2</sub>)<sub>2</sub>(PO<sub>4</sub>)<sub>2</sub>·10-12H<sub>2</sub>O (sample ICSM15-02) was obtained from the chernikovite
- 73 sample by cationic exchange, whereby 0.5 g of chernikovite was treated at 40°C with a 2 mol/L CaCl<sub>2</sub>
- 74 solution for 30 days at a stoichiometric ratio Ca/U = 80. The complete exchange of the protons for  $Ca^{2+}$
- ions was controlled by X-ray diffraction. Similarly, ankoleite, K(UO<sub>2</sub>)PO<sub>4</sub>·6H<sub>2</sub>O (sample ICSM15-01) was

- 76 obtained by immersing the chernikovite precursor in 1 mol/L KNO<sub>3</sub> solution for 7 days at a 77 stoichiometric ratio K/U = 2 [S6].
- 78 Synthetic (meta-)torbernite, (H<sub>3</sub>O)<sub>0.4</sub>Cu<sub>0.8</sub>(UO<sub>2</sub>)<sub>2</sub>(PO<sub>4</sub>)<sub>2</sub>·7.6H<sub>2</sub>O (sample ICSM15-05) was obtained by
- 79 direct precipitation in one step. 85 mL of 0.2 mol/L uranyl nitrate solution (pH = 1.1) containing 1.46 g
- 80 of CuCl<sub>2</sub>·2H<sub>2</sub>O was mixed with 8.5 mL of 2 mol/L H<sub>3</sub>PO<sub>4</sub> solution [S7]. After 3 days of maturation at
- 81 60°C, the precipitate was recovered by centrifugation, then washed three times with deionised water
- 82 and once with ethanol. The samples were then dried for 24 h at 40°C.

#### S.1.4. Uranium sulfates 83

84 Synthetic zippeite,  $K_3(UO_2)_4(SO_4)_2O_3(OH)\cdot 3H_2O$  (sample SBb-005) and synthetic Na-zippeite 85  $Na_5(UO_2)_8(SO_4)_4O_5(OH)_3$ ·12H<sub>2</sub>O (sample SBb-015) were obtained using hydrothermal conditions 86 following a protocol inspired from Sharifironizi et al. [S8], whereby 0.248 g of uranyl acetate and 0.056 87 g of potassium sulfate or sodium sulfate were dissolved in 4 mL of deionised water. The resulting 88 solution was placed in a 23 mL Teflon-lined Parr reaction vessel. The pH of the solution was adjusted 89 to 4.35 using 1 mol/L KOH or NaOH solution. Then, the reaction vessels were closed and heated at 90 150°C for 3 days in an oven. After cooling, the solid was washed three times with deionised water and 91 once with ethanol by centrifugation in 40 mL of solvent. The samples were then dried for 24 h at 60°C.

#### 92 S.1.5. Uranium silicates

- 93 Synthetic soddyite,  $(UO_2)_2(SiO_4) \cdot 2H_2O$  (sample SBb-004) was prepared following the protocol described
- 94 by Casas et al. [S9]. 20 mL of a solution of uranyl nitrate at 0.148 mol/L was added to 5 mL of sodium 95 metasilicate solution at 0.074 mol/L. The pH of the resulting solution was adjusted to 4.4 by addition
- 96 of a 4 mol/L HCl solution. The mixture was stirred at room temperature for 100 hours, then was heated
- 97 under reflux at 80°C for 6 h. The precipitate was separated from the solution by filtration and washed
- 98 with a large quantity of boiling deionised water. The precipitate was dried in an oven at 90°C for 24 h,
- 99 then placed in a 23 mL Teflon-lined Parr reaction vessel with 15 mL of deionised water. The reaction
- 100 vessel was closed and placed in an oven at 130°C for 2 weeks. After cooling, the solid phase was washed
- 101 three times with deionised water and once with ethanol by centrifugation in 40 mL of solvent. The
- 102 sample was then dried for 24 h at 60°C.
- 103 Synthetic weeksite,  $K_2(UO_2)_2(Si_5O_{13})\cdot 4H_2O$  (sample SBb-019) was obtained using a protocol adapted 104
- from Vochten et al. [S10], initially designed for the synthesis of boltwoodite. Thus, 25 mL of a solution
- 105 containing 0.133 mol/L uranyl nitrate, 0.269 mol/L of KCl and 0.287 mol/L of silica (Ludox AM silica
- 106 colloidal, 30 wt.%, Sigma Aldrich) was prepared. The pH of the reactive medium was 11.4. This solution
- 107 was then placed in a 45 mL Teflon-lined Parr autoclave and heated at 185°C for 21 days. After cooling,
- 108 the precipitate was washed three times with deionised water and once with ethanol by centrifugation
- 109 in 40 mL of solvent. The sample was then dried for 24 h at 60°C.
- 110 Synthetic boltwoodite, K(UO<sub>2</sub>)(SiO<sub>3</sub>OH)·1.5H<sub>2</sub>O (sample SBb-006) was prepared following a protocol 111 adapted from Vochten et al. [S10]. 25 mL of a solution containing 0.136 mol/L of uranyl nitrate, 0.275
- 112 mol/L of KCl and 2 mol/L of silica (quartz fine granular, Supelco) was prepared. The pH of the reactive
- 113 medium was 12. This solution was then placed in a 45 mL Teflon-lined Parr autoclave and heated at
- 114 185°C for 21 days. After cooling, the precipitate was washed three times with deionised water and
- 115 once with ethanol by centrifugation in 40 mL of solvent. The sample was then dried for 24 h at 60°C.
- 116 Synthetic calcium uranyl silicate hydrate, Ca<sub>2</sub>(UO<sub>2</sub>)<sub>2</sub>(Si<sub>2</sub>O<sub>5</sub>)<sub>3</sub>·10 H<sub>2</sub>O (sample SBb-020) was obtained by
- 117 mixing 25 mL of a solution of a 0.188 mol/L uranyl nitrate with 5 mL of 0.456 mol/L calcium nitrate
- 118 solution and 15 mL of 0.3 mol/L sodium metasilicate solution. The pH of the resulting mixture was 10.4.
- 119 The mixture was stirred at room temperature for 30 days. Then, it was heated under reflux at 90°C for

120 24 h. The precipitate was separated from the solution by filtration and washed with a large quantity of 121 boiling deionised water. The precipitate was dried in a vacuum at room temperature, then placed in a 122 45 mL Teflon-lined Parr reaction vessel with 30 mL of deionised water. The reaction vessel was closed 123 and placed in an oven at 120°C for 2 weeks. After cooling, the solid phase was washed three times with 124 deionised water and once with ethanol by centrifugation in 40 mL of solvent. The sample was then 125 dried for 24 h at 60°C.

126 Synthetic sodium uranyl silicate hydrate, Na<sub>2</sub>(UO<sub>2</sub>)<sub>2</sub>(Si<sub>2</sub>O<sub>5</sub>)<sub>3</sub>·10H<sub>2</sub>O (sample SBb-014) was obtained 127 following a protocol initially proposed by Wall et al. [S11] for synthesizing Na-boltwoodite. 3 mL of a 128 0.1 mol/L sodium acetate solution was mixed with 30 mL of a 0.01 mol/L uranyl acetate solution. 3 mL 129 of a 0.1 mol/L solution of sodium metasilicate at pH 10 was added to this mixture. The pH of the 130 reacting medium was adjusted to 10 by adding 1 mol/L NaOH solution. The reacting medium was 131 placed in a PFA reactor (Savillex<sup>®</sup>), hermetically sealed and then heated at 90°C in an oven for 2 days. 132 The precipitate formed was separated from the supernatant by centrifugation, then immersed in 30 133 mL of deionised water in a 45 mL Teflon-lined reaction vessel. The autoclave was closed and heated at 134 135°C during 7 days in an oven. After cooling, the solid phase was washed three times with deionised 135 water and once with ethanol by centrifugation in 40 mL of solvent. The sample was then dried for 24 136 h at 60°C.

137 Synthetic Uranophane- $\alpha$ , Ca(UO<sub>2</sub>)<sub>2</sub>(SiO<sub>3</sub>OH)<sub>2</sub>·5H<sub>2</sub>O (sample EA21-064) was obtained by mixing 15 mL 138 of 0.307 mol/L sodium metasilicate solution with 5 mL of 0.461 mol/L calcium chloride solution. Then, 139 this mixture was added to 20 mL of 0.228 mol/L uranyl nitrate solution. The pH of the reacting mixture 140 was adjusted to 8.5 by adding ammonia. The reacting mixture was stirred for 4 hours at room 141 temperature. These steps were made in an inert-gas (Ar) glove box. Then, the reacting mixture was 142 transferred from the glove box into a sealed flask and refluxed in an Ar atmosphere at 80°C for 24 h. 143 The precipitate was separated from the supernatant and washed with deionised water by 144 centrifugation before being placed in a 23 mL Teflon-lined Parr vessel with 11 mL of deionised and 145 decarbonated water. The autoclave was also closed in the Ar glove box. The autoclave was then heated 146 at 120°C for 21 days in an oven. After cooling, the solid phase was washed three times with deionised 147 water and once with ethanol by centrifugation in 40 mL of solvent. The sample was then dried for 24 148 h at 60°C.

## 149 **S.1.6. Uranium carbonates**

- The synthesis of carbonate phases was done following the synthesis of liebigite  $(Ca_2UO_2(CO_3)_3 \cdot 10H_2O)$ described by Meyrowitz [S12]. A solution of 5.02 g of  $UO_2(NO_3)_2 \cdot 6H_2O$  in 10 mL water was slowly added to a solution of 3.18 g of anhydrous  $Na_2CO_3$  in 100 mL water under constant agitation. A solution of 4.72 g of  $Ca(NO_3)_2 \cdot 4H_2O$  in 10 mL water was then slowly added to the uranyl carbonate solution under agitation. After pH adjustment to 8-8.2 with an  $Na_2CO_3$  solution, a solid was precipitated (fine powder) after 24 hours. The solid was separated from solution using a Buchner filter. The equilibrium solution
- was left to rest in a closed vessel. After two weeks a second solid (well-formed crystals) was precipitated. The XRD analyses showed mainly liebigite with andersonite (Na<sub>2</sub>CaUO<sub>2</sub>(CO<sub>3</sub>)<sub>3</sub>·6H<sub>2</sub>O) in the first solid with remaining Ca(NO<sub>3</sub>)<sub>2</sub>·4H<sub>2</sub>O and calcite (CaCO<sub>3</sub>); the second solid was mainly composed of andersonite with liebigite.
- 160This was supported by SEM analyses (see ) that showed crystals of liebigite and andersonite similar to161Vochten et al. [S13], but also of a third phase recalling the identification of a162 $Ca_{1.54}Na_{0.63}[UO_2(CO_3)_3] \cdot xH_2O$  lath phase by Vochten et al. [S14].
- 163

#### 164 S.1.7. Adsorption of uranyl on clays

165 Raw bentonite MX80 and purified clay materials used in previous works were conditioned following a 166 protocol already described for bentonite MX80 [S15], Na-kaolinite [S16], Na-smectite [S17] and Na-167 illite du Puy [S18]. For sorption experiments, about 100 mg of clay material was first dispersed in 20 168 mL of 5.10<sup>-2</sup> mol/L NaClO<sub>4</sub> solution in a 50 mL centrifuge tube (Corning<sup>®</sup>, polypropylene). The tubes 169 were placed at room temperature on a roller shaker for 16 h to equilibrate the clay with the solution. 170 After phase separation by centrifugation at 20 000 rpm for 20 min, the pH of the solution was 171 measured. The pH at equilibrium was found to vary between 7.15 and 7.91 for Na-kaolinite and Na-172 illite, between 7.95 and 9.1 for Na-smectite and between 8.83 and 9.37 for MX80. Then, the solid phase 173 was dispersed and the solutions were spiked with various amounts of a certified uranium standard 174 solution in 1 % HNO<sub>3</sub> (1 g/L or 10 g/L PlasmaCAL single element calibration standard, SCP Science) to 175 reach initial uranium concentrations in the range between 10<sup>-4</sup> and 2×10<sup>-7</sup> mol/L. The pH of the 176 suspensions was measured after addition of the uranium solutions and adjusted if necessary to the 177 previous equilibrium value with 1 mol/L NaOH. Then, the suspensions were equilibrated for 24 h on a 178 roller shaker. After separation of the solid and liquid phases by centrifugation at 20000 rpm for 20 min, 179 10 mL of solution was sampled to measure the remaining U elemental concentration. After 180 acidification with concentrated HNO<sub>3</sub> solution (65 % HNO<sub>3</sub> Suprapur, for trace analysis, Merck), the U 181 elemental concentration was analysed in the collected samples by an inductively coupled plasma mass 182 spectrometry (ICP-MS) (iCAP RQ, Thermo Fisher). The ICP-MS was calibrated for U using several 183 standard solutions prepared by dilution of a single element standard solution at 1 g/L (PlasmaCAL, SCP 184 Science) in 1 % HNO<sub>3</sub> solution (Suprapur, for trace analysis, Merck). The elemental concentration of 185 uranium was calculated as the average of three replicates at mass 238. Under these analytical 186 conditions, the detection limit for uranium reached 1×10<sup>-10</sup> mol/L. The relative experimental error was 187 calculated as twice the relative standard deviation of the three replicates and was less than 3 %.

188 The concentration of U adsorbed on the clay material surface,  $C_s^U$  in ppm was then calculated as 189 follows:

190 
$$C_s^U = \frac{(C_0^U - C_{eq}^U)}{m_{clay}} \times V$$
(1)

191 With  $C_0^U$ , U initial concentration in mg/L,  $C_{eq}^U$ , U concentration at equilibrium in mg/L, V, volume of 192 solution in L, m<sub>clay</sub> mass of the sample in kg.

Table S.1 gives the calculated adsorbed U concentration of the clay samples used in the training,validation and test sets.

**196** Table S.1 List of clay samples used in this study, concentration of the uranium contact solution  $C_0^{U}$ , mass of clay

**197** material ( $\pm$  0.1 mg), pH after addition of U solution ( $\pm$  0.1), U elemental concentration in solution after 24 h of

198 contact with clay material  $C_{eq}^{U}$  (± 5 %), and calculated U concentration sorbed on the clay surface  $C_{s}^{U}$  (± 10 %). 199 The sample set in which each sample is used for chemometric treatment is indicated in the last column.

Clay	Reference	C₀ <sup>∪</sup>	рΗ	m <sub>clay</sub>	V	$C_{eq}^{U}$	<b>C</b> <sub>s</sub> <sup>U</sup>	
material		(mol/L)		(mg)	(mL)	(mol/L)	(ppm)	Sample set
	EA21-01	1.12×10 <sup>-6</sup>	9.6	101.9	20	2.14×10 <sup>-7</sup>	42	Validation set
MX80	EA21-02	7.32×10 <sup>-6</sup>	9.8	97.8	20	1.41×10 <sup>-6</sup>	288	Validation set
IVIAOU	EA21-03	9.89×10 <sup>-5</sup>	9.2	99.2	20	1.90×10 <sup>-5</sup>	3834	Test set
	EA-21-018	9.17×10 <sup>-6</sup>	8.9	100.7	20	6.84×10 <sup>-6</sup>	110	Validation set
	EA21-04	1.72×10 <sup>-6</sup>	7.1	102.3	20	3.31×10 <sup>-7</sup>	65	Validation set
Na-illite	EA21-05	1.23×10 <sup>-5</sup>	7.6	101.8	20	2.36×10 <sup>-6</sup>	463	Training set
Na-IIIIte	EA-21-021	3.1×10 <sup>-7</sup>	7.2	101.7	20	7×10 <sup>-10</sup>	15	Validation set
	EA-21-025	1.25×10 <sup>-6</sup>	7.5	101.4	20	5.62×10 <sup>-8</sup>	56	Validation set
	EA21-07	1.57×10 <sup>-6</sup>	8.7	99.5	20	3.01×10 <sup>-7</sup>	61	Validation set
	EA21-08	8.99×10 <sup>-6</sup>	8.7	102.7	20	1.73×10 <sup>-6</sup>	336	Training set
Na-kaolinite	EA-21-027	3.1×10 <sup>-7</sup>	7.1	101.7	20	2.8×10 <sup>-9</sup>	15	Validation set
Na-kaomme	EA-21-029	1.94×10 <sup>-5</sup>	7.8	100.6	20	9.44×10 <sup>-6</sup>	471	Training set
	EA-21-030	9.17×10 <sup>-6</sup>	7.7	101.4	20	1.27×10 <sup>-6</sup>	371	Validation set
	EA-21-032	2.5×10 <sup>-7</sup>	7.1	102.1	20	4.2×10 <sup>-9</sup>	11	Validation set
	EA21-10	1.80×10 <sup>-6</sup>	9.4	98.8	20	3.46×10 <sup>-7</sup>	70	Validation set
	EA21-11	1.21×10 <sup>-5</sup>	9.4	99.5	20	2.32×10 <sup>-6</sup>	466	Validation set
Na-smectite	EA-21-035	1.94×10 <sup>-5</sup>	8.6	99.7	20	6.17×10 <sup>-7</sup>	897	Training set
	EA-21-036	9.17×10 <sup>-6</sup>	8.9	98	20	2.42×10 <sup>-8</sup>	444	Training set
	EA-21-038	2.5×10 <sup>-7</sup>	9.1	98.2	20	7.7×10 <sup>-9</sup>	12	Validation set

200

## 201 S.2. Characterisations of the synthetic samples

The synthetic samples were systematically characterised by Powder X-ray diffraction (PXRD) and Scanning Electron Microscopy (SEM). PXRD patterns were recorded using a Bruker D8 Advance diffractometer with copper radiation ( $\lambda$ Cu K $\alpha_{1,2}$  = 1.54184 Å) in a parallel mode and using the reflection geometry. The patterns were recorded between 5° and 100° (2 $\theta$ ) with a step of 0.02 ° and a counting time of 3 h. The PDF-2 release 2015 database (ICDD) was used to identify the prepared phase. Figure S.1 shows PXRD patterns of most synthetic samples used in the training dataset and of two samples of the validation dataset.

209 The Raman spectra were recorded with a Horiba-Jobin Yvon Aramis apparatus using a Nd:YAG laser 210 (532 nm) delivering 60 mW power at the sample surface and associated edge filter. The laser beam 211 was focused on the sample by an Olympus BX 41 microscope, with a spot size of about 1  $\mu$ m<sup>2</sup>. For each 212 spectrum, a dwell time of 10 s and an average of four scans was used. FTIR spectra in the ATR mode 213 were recorded in the 500–4000 cm<sup>-1</sup> range thanks to a Perkin-Elmer FTIR Spectrum 100 device. 214 Powdered samples were deposited on the surface of an ATR crystal without any prior preparation. The 215 spectra collected in such operating conditions exhibited a resolution lower than 4 cm<sup>-1</sup>. The Raman 216 and IR spectra of the synthetic samples can be made available on request.

- 217 The scanning electron microscopy (SEM) analyses were conducted using a Quanta 200 ESEM FEG (FEI
- 218 Company) electron microscope equipped either with a backscattered electron detector (BSED) in high
- vacuum conditions or with a secondary electron detector (SED) with a 25 kV accelerating voltage.

220 Figure S.2 shows one SEM/BSE micrograph for most synthetic samples used in the training and 221 validation sets. The powders were directly analyzed without any preparation. X-ray energy dispersive 222 spectroscopy (X-EDS) analyses were performed under the same conditions using the Bruker AXS X-223 Flash 5010 detector coupled to the SEM device. X-EDS spectra were obtained using the same detector 224 and operating conditions. For that purpose, an aliquot of each sample was embedded in an epoxy 225 resin, polished to optical grade and metalized by carbon deposition. 20 to 40 X-EDS measurements 226 were performed for each sample. The average elemental concentration as well as twice the standard 227 deviation are compiled in Table S.2 for most synthetic samples.


The composition of andersonite and liebigite (samples LANIE15-01 and LANIE 15-02) was determined by inductively coupled plasma atomic emission spectroscopy (ICP-AES) analyses after complete

dissolution of an aliquot of the sample in a 2 % HNO<sub>3</sub> solution. The ICP-AES device (Horiba Jobin Yvon)

was calibrated for U, Ca and Na using several standard solutions prepared by dilution of single element

standard solutions at 1 g/L in a 2 % HNO<sub>3</sub> solution. The recommended emission wavelengths of the

- 233 elements were all considered in the analytical procedure. From the elemental concentrations in
- solution, the U, Ca and Na mass fractions of the samples were calculated. The obtained results as well
- as twice the standard deviation are given in Table S.3.








Figure S.1 Powder XRD patterns of some synthetic samples used in the training and validation sets compared to references from the PDF-2 release 2015 ICDD database. (a) Samples from the oxides and hydrated oxides family ( $UO_3 nH_2O$  with n = 0, 0.8, 2); (b) samples from the oxide-hydroxy-hydrates family (billietite, compreignacite and becquerelite); (c) samples from the phosphates family (chernikovite, ankoleite, metaautunite and meta-torbernite); (d) sample from the vanadates family (carnotite); (e) samples from the sulfates family (zippeite and Na-zippeite); (f) samples from the silicates family (uranophane- $\alpha$  and calcium uranyl silicate); (g) samples from the silicates family (boltwoodite and weeksite); (h) samples from the silicates family (soddyite and sodium uranyl silicate); (i, j) samples from the carbonates family (andersonite, liebigite); (k) commercial uranyl salts (acetate, nitrate and sulfate).





243

246 Figure S.2 SEM micrographs (BSE mode) of some synthetic samples used in the training and validation sets. (a)

247 Samples from the hydrated oxides family ( $UO_3 nH_2O$  with n = 0.8, 2); (b) samples from the oxide-hydroxy-

248 hydrates family (billietite, compreignacite and becquerelite); (c) samples from the phosphates family

249 (chernikovite, ankoleite, meta-autunite and meta-torbernite); (d) sample from the vanadates family (carnotite);

250 (e) samples from the sulfates family (zippeite and Na-zippeite); (f) samples from the silicates family

251 (uranophane- $\alpha$  and calcium uranyl silicate); (g) samples from the silicates family (boltwoodite and weeksite); (h) 252 samples from the silicates family (soddyite and sodium uranyl silicate); (i) samples from the carbonates family

253 (andersonite and liebigite).

Table S.2 X-EDS analyses of some synthetic samples used in the training and validation sets. The indicated atomic percentages were calculated as the average of at least 20 X EDS measurements. 2σ stands for twice the standard deviation and is related to the spatial heterogeneity of the composition.

Sample					Eleme	ntal composi	tion (at.%	ώ±2σ)			
reference	Sample name	U	Ва	Са	Cu	К	Na	S	Si	Р	v
ICSM15-01	ankoleite	33 ± 1				32 ± 3				35 ± 1	
ICSM15-02	autunite	42 ± 1		22 ± 2						36 ± 1	
ICSM15-05	torbernite	42 ± 1			14 ± 3					44 ± 2	
ICSM15-03	carnotite	36 ± 2				29 ± 3					35 ± 3
EA21-055	becquerelite	85 ± 6		15.0 ± 0.2							
EA21-048	becquerelite	91 ± 2		8.9 ± 1.7							
EA21-049	billietite	86.6 ± 0.7	13.7 ± 0.7								
EA21-050	compreignacite	83.5 ± 0.9				16.5 ± 0.9					
SBb-015	Na-zippeite	58 ± 1					24 ± 1	17.1 ± 0.3			
SBb-005	zippeite	61 ± 1				21 ± 2		17.7 ± 0.6			
SBb-020	Ca and U silicate	39 ± 2		12 ± 2					49 ± 2		
SBb-004	soddyite	49 ± 2							51 ± 17		
EA21-064	uranophane	51 ± 5		11.7 ± 0.2					38 ± 1		
SBb-019	weeksite	22 ± 3				14 ± 5			64 ± 7		
SBb-006	boltwoodite	30 ± 15				25 ± 10			45 ± 20		
SBb-014	Na and U silicate	41 ± 11					19 ± 7		37 ± 11		

257

258 Table S.3 Elemental composition of synthetic samples of the carbonates family determined by ICP-AES analyses after total dissolution of the samples.

		Elementa	al composition	(wt.% ± 2σ)
Sample reference	Sample name	U	Са	Na
LANIE15-01	andersonite	36 ± 1	25 ± 1	9 ± 1
LANIE15-02	liebigite	37 ± 1	35 ± 1	6 ± 1

# 260 S.3. Prediction results on the training set

#### 261 Table S.4 Mineralogical family predicted by model 1 on the training dataset, expressed as a rate over the total number of spectra for each sample.

SAMPLE : MINERALO- GICAL FAMILY .	Metazeunerite	Andersonite	Llebigite Illite A05		Kaolinite 008	Kaolinite 029	Smectite 035	Smectite 036	Acetate	Nitrate	Metaschoepite	Paraschoepite	UO3	Becquerelite 055	Billietite 049	Compreignacite 050	Ankoleite	Autunite	Autunite (synthetic)	Chernikovite	Torbernite (BN42)	Torbernite (synthetic)	Ca and U silicate	Soddyite	Uranophane 064	Weeksite	Na Zippeite	Sulfate	Zippeite	Carnotite	Francevillite
Reference : Predicted :	Arsenates	Carbonates				Clays			Other			Oxides			<b>Oxy-hydroxides</b>				Dhochatac					Cilicotoc	ollicates			Sulfates		1. and a to a	vallauates
Arsenates	0.9 6		0.0	)4																											
Carbonates		1	1																												
Clays			0.9	92	1	1	1 (	0.96																							
Other									1	1																					
Oxides											1	1	1																		
Oxy-hydroxides														1	1	1															
Phosphates	0.0 4																1	1	1	1	1	1									
Silicates																							1	1	1	1					
Sulfates			0.0	)4			(	0.04																			1	1	1		
Vanadates																														1	1

### 263 Table S.5 Sample predicted by model 2 on the training dataset, expressed as a rate over the total number of spectra for each sample.

Reference : Predicted :	Acetate Andersonite	Ankoleite Autunite	Autunite Autunite (synthetic)	Becquerelite 055	Billietite 049	Ca and U silicate	Carnotite	Chernikovite	Compreignacite 050	Francevillite	Illite 005	Kaolinite 008	Kaolinite 029	Liebigite	Metaschoepite	Metazeunerite	Na Zippeite	Nitrate	Paraschoepite	Smectite 035	Smectite 036	Soddyite	Sulfate	Torbernite (BN42)	Torbernite (synthetic)	UO3	Uranophane 064	Weeksite Zippeite
Acetate	1																											
Andersonite	1																											
Ankoleite		1																										
Autunite		1	_													0.04												
Autunite (synthetic)			1																									
Becquerelite 055				0.88				(	0.04																			
Billietite 049					0.96																							
Ca and U silicate						1																						
Carnotite							1																					
Chernikovite								1																				
Compreignacite 050				0.12	0.04			(	0.96																			
Francevillite										1																		
Illite 005											0.92																	
Kaolinite 008												0.96																
Kaolinite 029												0.04	0.92															
Liebigite														1														
Metaschoepite															1													
Metazeunerite											0.04					0.96												
Na Zippeite																	1				0.04							
Nitrate																		1										
Paraschoepite																			1									
Smectite 035																				1								
Smectite 036																					0.96							
Soddyite																						1						
Sulfate																							1					
Torbernite (BN42)																								1				
Torbernite (synthetic)																									1			
UO3																										1		
Uranophane 064																											1	
Weeksite																												1
Zippeite											0.04																	1

### 265 **S.4. References**

- 266
- [S1] Cordfunke, E.H.P. and P. Aling, Thermal Decomposition Of Hydrated Uranium Peroxides. Recueil
  Des Travaux Chimiques Des Pays-Bas-Journal of the Royal Netherlands Chemical Society, 1963.
  82(3): p. 257.
- [S2] Vochten, R. and L. Vanhaverbeke, Transformation of schoepite into the uranyl oxide hydrates becquerelite, billietite and wolsendorfite. Mineralogy and Petrology, 1990. 43(1): p. 65-72.
- [S3] Abraham, F., C. Dion, and M. Saadi, Carnotite analogues: synthesis, structure and properties of
  the Na<sub>1-x</sub>K<sub>x</sub>UO<sub>2</sub>VO<sub>4</sub> solid solution (0< x<1). Journal of Materials Chemistry, 1993. 3(5): p. 459-463.</li>
- [S4] Crétaz, F., Etude de la solubilité et des cinétiques de dissolution des phosphates et vanadates d'uranium : Implications pour l'amont du cycle électronucléaire. 2013, Université Montpellier II.
   p. 243.
- [S5] Vochten, R. and M. Deliens, Transformation of curite into metaautunite paragenesis and electrokinetic properties. Physics and Chemistry of Minerals, 1980. 6(2): p. 129-143.
- [S6] Clavier, N., et al., Vibrational spectroscopy of synthetic analogues of ankoleite, chernikovite and intermediate solid solution. Spectrochimica acta. Part A, Molecular and biomolecular spectroscopy, 2016. 156: p. 143-50.
- [S7] Cretaz, F., et al., Solubility properties of synthetic and natural meta-torbernite. Journal of
  Nuclear Materials, 2013. 442(1-3): p. 195-207.
- [S8] Sharifironizi, M., et al., Thermodynamic studies of zippeite, a uranyl sulfate common in mine
  wastes. Chemical Geology, 2016. 447: p. 54-58.
- [S9] Casas, I., et al., Dissolution studies of synthetic soddyite and uranophane. SKB Technical Report,
  1997. 97-15: p. 36.
- [S10] Vochten, R., et al., A new method of synthesis of boltwoodite and of formation of sodium
  boltwoodite, uranophane, sklodowskite and kasolite from boltwoodite. Canadian Mineralogist,
  1997. 35: p. 735-741.
- [S11] Wall, N.A., S.B. Clark, and J.L. McHale, Synthesis and characterization of 1:1 layered uranyl
  silicate mineral phases. Chemical Geology, 2010. 274(3-4): p. 149-157.
- [S12] Meyrowitz, R., Liebigite, in Systematic Mineralogy of Uranium and Thorium. U.S. Geological
  Survey Bulletin 1064 (1958), C. Frondel, Editor. 1954: Washington. p. 109-112.
- [S13] Vochten, R., L. Van Haverbeke, and K. Van Springel, Synthesis of liebigite and andersonite, and
  study of their thermal behavior and luminescence. The Canadian Mineralogist, 1993. 31(1): p.
  167-171.
- [S14] Vochten, R., et al., The structure and physicochemical characteristics of a synthetic phase
  compositionally intermediate between liebigite and andersonite. The Canadian Mineralogist,
  1994. 32: p. 553-561.
- 301 [S15] Bernachy-Barbe, F., Homogenization of bentonite upon saturation: Density and pressure fields.
  302 Applied Clay Science, 2021. 209: p. 106122
- 303 [S16] Reinoso-Maset, E. and J. Ly, Study of uranium(VI) and radium(II) sorption at trace level on
  304 kaolinite using a multisite ion exchange model. Journal of Environmental Radioactivity, 2016.
  305 157: p. 136-148.
- [S17] Orucoglu, E., et al., From experimental variability to the sorption related retention parameters
  necessary for performance assessment models for nuclear waste disposal systems: The example
  of Pb adsorption on clay minerals. Applied Clay Science, 2018. 163: p. 20-32.
- 309 [S18] Asaad, A., et al., A baseline study of mineralogical and morphological properties of different size
  310 fractions of illite du Puy. Applied Clay Science, 2022. 224: p. 106517.
- 311