

Utilization of tomography data for process improvement in additive manufacturing through cross-correlation with real time monitoring data

Jitendra-Singh Rathore, Xavier Setoain, Philippe Bredif, Vincent Bergeaud, Adrien Stolidi, Marius Costin

► To cite this version:

Jitendra-Singh Rathore, Xavier Setoain, Philippe Bredif, Vincent Bergeaud, Adrien Stolidi, et al.. Utilization of tomography data for process improvement in additive manufacturing through crosscorrelation with real time monitoring data. iCT2023 - 12th International Conference on Industrial Computed Tomography, Feb 2023, Fürth, Germany. , 2023. cea-04256609

HAL Id: cea-04256609 https://cea.hal.science/cea-04256609

Submitted on 24 Oct 2023 $\,$

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Utilization of X-ray tomography data for process improvement in additive manufacturing through cross-correlation with real time **monitoring data**

Jitendra Singh Rathore¹, Setoain Imanol¹, Philippe Brédif¹, Vincent Bergeaud¹, Adrien Stolidi¹, Marius Costin¹

¹Université Paris-Saclay, CEA, List, F-91190, Palaiseau, France

Introduction

list

SSS

- Additive Manufacturing (AM) parts are often subject to defects which are induced from one or more undesirable variations in the process parameters.
- The process monitoring data are available from the machines but there is a lack of strategies about how this can be used in a meaningful way.
- CIVA is a software consisting of several model related to different NDT techniques
- The "RT" model consists of a number of capabilities





Methodology

MANUFACTURING

- Additive manufacturing samples are produced with intentional varitions in the process parameters
- The process data is recorded on the time scale
- A file containing monitoring data in a standardized Hierarchical Data Format (HDF5)

X-RAY CHARACTERIZATION

- The tomography acquisition are peformed with an inhouse robotic CT system
- A tomography file reconstructed file in the raw format



The indication table (defect analysis) as CSV file

CIVA DEVELOPLMENT

- Registration of the different files in a common frame
- Annotation of the monitoring files to specify the time ranges corresponding to the different AM layers

165 kV

180 µA

- Analysis of the monitoring files via inter-layer comparison
- Analysis of the monitoring files via comparison with tomographic data



New "AM" module

- The first version of the module is developed containing different tools
- Several validations are being performed



• Annotation of monitoring data

To be able to adapt to a majority of cases, this module has three tools to perform the temporal cutting of the data:

Regular Cut aims at positioning the layers by taking a regular hypothesis (identical manufacturing time for each layer)

First results on metallic AM

- A metallic mock-up produced from wire arc additive manufacturing process
- 900 projections Several parts were produced with intentional process variation inducing defects
- There are always high variations observed in the process parameters at the start and end of a layer
- An example of an defective layer and a health layer is shown





- Z Analysis allows layers to be positioned automatically with each variation in the Z-height signal
- Threshold allows the layers to be positioned semi-automatically each time a given threshold is crossed



Inter-layer comparisons

- 3D representation with a colour map in order to spot the outlying values observed during the process
- 2D representation in order to focus on a given layer
- Statistical analysis for each layer in order to compare the layers and identify the layers containing abnormal values

XY coordinate

XYZ coordinates

- A metallic wall shaped part is produced from WAAM process
- The defects are well characterized with tomography
- The process data is however nominal here
- There is a good correspondence between local process variations and defects





Future work



A new experimental campaign is ongoing for nanocomposites produced through FDM (Fused Deposition Modelling) AM process

The first tomography results revealed that the defects are indeed layer-wise distributed



CONCLUSIONS

- The work is an attempt towards the development of software module for AM process enhancement within CIVA framework
- It has been demonstrated that there are correspondence between the real time micro process variations and the defects
- This is an important step towards AM process improvement
- The module is being validated on several applications







This work is being carried within the framework of INTEGRADDE and BIONANOPOLYS project which has received funding from the European Union's Horizon 2020 research and innovation program under grant agreement No 820776 and No 953206 respectively.



12th CONFERENCE ON INDUSTRIAL **COMPUTED TOMOGRAPHY 2023** February 27 - March 2 FÜRTH, GERMANY