

Curved hexahedral block structure generation by advancing front

Claire Roche, Jérôme Breil, Simon Calderan, Thierry Hocquellet, Franck Ledoux

▶ To cite this version:

Claire Roche, Jérôme Breil, Simon Calderan, Thierry Hocquellet, Franck Ledoux. Curved hexahedral block structure generation by advancing front. SIAM IMR24 - SIAM International Meshing Roundtable Workshop 2024, SIAM, Mar 2024, Baltimore, United States. cea-04505745

HAL Id: cea-04505745 https://cea.hal.science/cea-04505745v1

Submitted on 15 Mar 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Curved Hexahedral Block-Structure Generation by Advancing Front

SIAM IMR 2024, 7 march, 2024

C. Roche^{1,3} (claire.roche@cea.fr)

J. Breil¹ (jerome.breil@cea.fr)

S. Calderan² (simon.calderan@cea.fr)

T. Hocquellet¹ (thierry.hocquellet@cea.fr)

F. Ledoux^{2,3} (franck.ledoux@cea.fr)

1 CEA-CESTA

² CEA, DAM, DIF, F-91297

³ LIHPC, CEA, UNIVERSITÉ PARIS-SACLAY

Context

Linear Block-Structure Generation

Fields Computation
Generation of One Block Layer
Conflict Management on a Layer
Examples of Linear Blocking

Bézier Block Curving

Block Curving Using Bézier Elements From Blocks to Final Mesh Examples of Final Meshes



Context

Linear Block-Structure Generation

Fields Computation
Generation of One Block Layer
Conflict Management on a Layer
Examples of Linear Blocking

Bézier Block Curving

Block Curving Using Bézier Elements From Blocks to Final Mesh Examples of Final Meshes



Context

This work aims to provide a solution to generate block-structured hexahedral meshes automatically for a legacy Computational Fluid Dynamics (CFD) code developed for atmospheric re-entry.




Fig. Flow around a supersonic vehicle

 Our meshing algorithm is freely available and implemented in the open-source C++ meshing framework GMDS [LWB]^a.

Ideal meshes:

- Near-wall orthogonality
- Thin cells in the boundary layer
- Smooth mesh size transition

Input meshes for the code:


Block-structured meshes

Hypotheses on the domain:

- Vehicles are completely immersed in the fluid
- Far-field is a smooth boundary
- ◆ Single-wall vehicle

 $a_{\tt https://github.com/LIHPC-Computational-Geometry/gmds.}$

Approach Overview



- Starting from a tetrahedral discretization of the domain (a)
- We first generate and combine distance fields (b)
- And build a vector field that ensure wall orthogonality and other properties (c)
- Using those fields, we generate a linear block structure (d)
- The block structure is curved using Bézier elements (e)
- And a final hexahedral mesh is generated (f)

Ruiz-Gironés E, Roca X, Sarrate J. The receding front method applied to hexahedral mesh generation of exterior domains. Engineering with computers, vol. 28, no. 4, 391-408, 2012.

Roche, C., Breil, J., Hocquellet, T., Ledoux, F. "Block-structured quad meshing for supersonic flow simulations". In SIAM International Meshing Roundtable Workshop 2023 (SIAM IMR 2023).



Context

Linear Block-Structure Generation

Fields Computation Generation of One Block Layer Conflict Management on a Layer Examples of Linear Blocking

Bézier Block Curving

Block Curving Using Bézier Elements From Blocks to Final Mesh Examples of Final Meshes



Fields Computation




Fig. a Euclidean Distance to the Vehicle d_{V}





Fig. c Combined Distance Field d=






Fig. d Vector Field

Generation of One Block Laver







Fig. b A Laver



Fig. c A new front

- Each face of the front (a) creates a hexahedral block by extrusion. This set of blocks is the layer (b).
- Each block corner of the front (a) computes the position of the next block corner in the next layer.



Fig. d Distance Field



Fig. e Vector Field




Fig. f Advected Block Corner



Fig. g New Blocks


➤ Need to solve conflicts due to expansion/contraction in a layer




Bézier Block Curving

Conflict Management on a Layer [RGRS12]

➤ Geometric classification of the edges of the front





Apply a set of patterns on edges and nodes of the front, according to the geometric classification of edges




Fig. f Edge Patterns

Fig. g Examples of Node Patterns

Fig. h Layer Generated on Front of Fig.e

[RGRS12] Ruiz-Gironés E, Roca X, Sarrate J. The receding front method applied to hexahedral mesh generation of exterior domains. Engineering with computers, vol. 28, no. 4, 391-408, 2012.

Linear Blocking around Double Ellipsoid [AADLC91]



Fig. a Double Ellipsoid Geometry

Fig. c Patterns on Second Layer of Blocks




Fig. d Layers of Linear Blocks

Fig. e Extrusion of Layers



Context

Linear Block-Structure Generation
Fields Computation
Generation of One Block Layer
Conflict Management on a Layer
Examples of Linear Blocking


Bézier Block Curving

Block Curving Using Bézier Elements From Blocks to Final Mesh Examples of Final Meshes




Block Curving Using Bézier Elements [Bez86, Feu19]

Aim: Improve the representation of the geometry to avoid the smoothing step on the final mesh.











Fig. b Bézier Curve of Degree p=3

Fig. c Linear Hexahedral Block

Fig. d Bézier Block of Degree p=2

- Control points of all the block faces corresponding to the surface of the geometry are computed to approximate the geometry surface
- Control points of the blocks adjacent to those faces are moved to avoid overlapping blocks






Fig. e Linear First Laver of Blocks

Fig. f Curved First Laver of Blocks

◆ For a more accurate and elegant way to process, you can attend the talk of KETAN MITTAL on "Mixed-Order Meshes through rp-Adaptivity for Surface Fitting to Implicit Geometries"

Interval Assignment: Set the Discretization of Each Block Edge




Fig. a Topological Sheet (III)

Topological Sheet

A set of opposite block edges.

 All edges of the same topological sheet share the same discretization

- ➤ For each topological sheet, an optimization problem is solved to compute the number of mesh edges of the block edges
- ➤ Each block is discretized uniformly in the parametric space of the Bézier Element







Fig. c Physical Space

Examples of Final Meshes

Linear Block-Structure Generation




Fig. c Mesh of RAMCII nose surface view from inside




Fig. d Mesh of RAMCII back surface view from inside




Fig. f Mesh around HyTRV geometry

Context

Linear Block-Structure Generation

Fields Computation
Generation of One Block Layer
Conflict Management on a Layer
Examples of Linear Blocking

Bézier Block Curving

Block Curving Using Bézier Elements From Blocks to Final Mesh Examples of Final Meshes





Conclusion & Perspectives

- This work proposed a solution to generate block-structured hexahedral meshes dedicated to CFD
- ♦ Extension of the work of Ruiz-Gironés et al. to high-order blocks

Perspectives

- Use the meshes generated for numerical simulations
- Improve the way to compute the curved blocks to approximate the surface of the geometry
- Work on curved blocks smoothing under constraints due to the applications




Fig. a Linear blocks around a geometry with wings




Fig. b The way the blocks are curved is not always sufficient to represent the geometry (■)





Thank you! Any question?



References I



D Aymer, T Alziary, Luigi De Luca, and G Carlomagno, Experimental study of the flow around a double ellipsoid configuration, Hypersonic Flows for Reentry Problems: Volume II: Test Cases—Experiments and Computations Proceedings of a Workshop Held in Antibes, France, 22–25 January 1990, Springer, 1991, pp. 335–357.



Pierre Bezier, Courbes et surfaces, mathématiques et cao, 4, Hermès, Paris (1986).



Rémi Feuillet, Embedded and high-order meshes: two alternatives to linear body-fitted meshes, Ph.D. thesis, Université Paris-Saclay, 2019.



Franck Ledoux, Jean-Claude Weill, and Yves Bertrand, Gmds: A generic mesh data structure.



Han Qi, Xinliang Li, Changping Yu, and Fulin Tong, Direct numerical simulation of hypersonic boundary layer transition over a lifting-body model hytrv, Advances in Aerodynamics 3 (2021), 1–21.



Eloi Ruiz-Gironés, Xevi Roca, and Josep Sarrate, The receding front method applied to hexahedral mesh generation of exterior domains, Engineering with computers 28 (2012), no. 4, 391–408.



Leonardo C Scalabrin, Numerical simulation of weakly ionized hypersonic flow over reentry capsules, Ph.D. thesis, Citeseer, 2007.



Annexes: 3D Surface Block Curving






Fig. d Initial control points on the faces

Fig. a Part of the geometric surface

Fig. b 2 blocks of the linear block structure

Fig. c Initial control points (elements of degree p=3), set uniformly on the linear blocks

corresponding to the geometric surface

Fig. e Points to interpolate on the geometric

surface (Fig. a), computed as the projection of

the control points of Fig. d onto the geometry





Fig. g Control points of the 2 Bézier elements

Fig. h Final mesh generated with the 2 Bézier elements defined by the control points of Fig. f

Bézier Quadrangle Expression in the Parametric Space

$$\forall u, v \in [0, 1], h(u, v) = \sum_{i=0}^{m} \sum_{j=0}^{n} B_{i}^{m}(u), B_{j}^{n}(v) P_{i,j}$$

where $P_{m,n}$ is the matrix of the control points, and m and n are the degree in each direction

As the first layer of blocks can be very thin, we add the same offset as the control points moved in **Fig. f** to the opposite face in the block. This step is not illustrated here and could be included between Fig. f and Fig. a.