



**HAL**  
open science

## Thermal design of PCM-RF Switches for 5G and beyond

Corentin Mercier, Gregory Tardy, Daniel Gheysens, Stéphane Monfray, Alain Fleury, Bruno Reig, Emmanuel Dubois, Jean-François Robillard

### ► To cite this version:

Corentin Mercier, Gregory Tardy, Daniel Gheysens, Stéphane Monfray, Alain Fleury, et al.. Thermal design of PCM-RF Switches for 5G and beyond. 1ères Journées Scientifiques du GDR CHALCO, Jun 2022, Dijon, France. , 2022. cea-04528379

**HAL Id: cea-04528379**

**<https://cea.hal.science/cea-04528379v1>**

Submitted on 1 Apr 2024

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

## Thermal design of PCM-RF Switches for 5G and beyond

C. Mercier<sup>1,2,3</sup>, G. Tardy<sup>1</sup>, D. Gheysens<sup>1,2</sup>, S. Monfray<sup>2</sup>, A. Fleury<sup>2</sup>, B. Reig<sup>3</sup>,  
E. Dubois<sup>1</sup>, J-F. Robillard<sup>1</sup>

<sup>1</sup>Univ. Lille, CNRS, Centrale Lille, Junia, Univ. Polytechnique Hauts-de-France, UMR 8520 - IEMN – Institut d'Electronique de Microélectronique et de Nanotechnologie, F-59000 Lille, France

<sup>2</sup>STMicroelectronics, 850 Rue Jean Monnet, 38920 Crolles

<sup>3</sup>CEA-LETI, 17 Av. des Martyrs, 38054 Grenoble

contacts : [jean-francois.robillard@iemn.fr](mailto:jean-francois.robillard@iemn.fr), [corentin.mercier@st.com](mailto:corentin.mercier@st.com)

### Abstract

Radiofrequency commutators (RF-Switches) are key components of front-end modules. This statement is reinforced with the introduction of 5G that implies selective propagation over a growing number of communications norms. Thus, switches of various power and extended frequency ranges are needed. Silicon-On-Insulator (RF-SOI) is currently the most popular technology for front-end RF modules [1]. This is thanks to its good tradeoff in terms of ON-state resistance  $R_{on}$  and OFF-state capacitance  $C_{off}$  leading to a metric  $f_c=1/(R_{on}C_{off})$  around 15 THz, breakdown voltage under high power and cost/performance ratio. Recently, Phase-Change Material technologies are emerging as a potential alternative [2-4]. These switches leverage the high electrical conductivity contrast ( $10^6$ ) between the amorphous and crystalline phases of a chalcogenide material such as GeTe. Their performance could increase  $f_c$  by a factor 5 with respect to RF-SOI. They also allow integration in the Back-End of Line at low cost. However, PCM-Switches require thermal optimization which sometimes contradicts the needs of electrical design. For example, the material between the RF-PCM channel and the heater should be an electrical insulator and a thermal conductor. Other significant parameters are the thermal couplings to the substrate and to the metallic RF contacts which will drive the dynamics of the switch. In this work, we present the design and modelling of an indirectly heated switch with a GeTe channel, and a tungsten resistive heater. A dielectric material ( $Si_3N_4$  or AlN) is used as the thermal coupler / electric insulator. We model the system with i) a lumped thermal model and ii) a Finite-Element Method software. The first method provides a quick and reasonable estimation of the response to voltages pulses. The second one is more accurate and provides detailed temperature maps and heat fluxes distribution during the transient phases. Results in terms of energy efficiency and dynamics show the strong impact of: heat spreading through the RF contacts, thickness of the dielectric spacer, temperature dependence of the heater resistivity and thermal boundary resistances.

### References

- [1] P. Chevalier *et al.*, "PD-SOI CMOS and SiGe BiCMOS Technologies for 5G and 6G communications," 2020 IEEE International Electron Devices Meeting (IEDM), 34.4.1-34.4.4
- [2] N. Wainstein *et al.* "Compact Modeling and Electrothermal Measurements of Indirectly Heated Phase-Change RF Switches," in *IEEE Transactions on Electron Devices*, **67**, 5182, (2020)
- [3] A. Léon *et al.* "High Performance and Low Energy Consumption in Phase Change Material RF Switches", *48th European Microwave Conference (EuMC)*, 491-494 (2018)
- [4] N.El-Hinnawy *et al.*, "12.5 THz Fco GeTe Inline Phase-Change Switch Technology for Reconfigurable RF and Switching Applications", in *Proc. IEEE Compound Semiconductor Integr. Circuit Symp. (CSICS)*, 1–3 (2014)