



Using universal target design in conjunction with accuracy and multiwavelength knobs for non-critical layer ov measurements on YS-S375

Yoann Blancquaert, Michael May, Jerome Depre, Maxime Cannac, Blandine Minghetti, Herman Heijmerikx

► To cite this version:

Yoann Blancquaert, Michael May, Jerome Depre, Maxime Cannac, Blandine Minghetti, et al.. Using universal target design in conjunction with accuracy and multiwavelength knobs for non-critical layer ov measurements on YS-S375. SPIE Advance Lithography + Patterning 2022, Feb 2022, San José, United States. cea-04654503

HAL Id: cea-04654503

<https://cea.hal.science/cea-04654503v1>

Submitted on 19 Jul 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Using Universal Target Design in conjunction with accuracy and multiwavelength knobs for non-critical layer OV measurements on YS-S375

Yoann Blancquaert ^{b*}, Michael May ^b, Maxime Cannac ^b
Jerome Depre ^a, Blandine Minghetti ^a, Herman Heijmerikx ^c

^aASML, Chemin de Pré Fontaine, Bernin, France

^bUniv. Grenoble Alpes, CEA, Leti, F-38000 Grenoble, France

^cASML, De Run 6501, 5504 DR Veldhoven, The Netherlands

ABSTRACT

Continued tightening of overlay control budget in semiconductor lithography drives the need for improved metrology capabilities. According to IRDS semiconductor roadmap, aggressive improvements are needed for overlay metrology in term of accuracy and precision to address below 5nm on product overlay specifications. However, cost reduction needs require a quick time to design target as well as a target reduction size without performance loss on the YieldStar YS-ASML metrology tools.

This study will present Overlay metrology results on a Universal target designed for the scatterometry based platform. A focus will be done on different KPIs (Key Performance Indicators): measurement accuracy and precision, residuals after a modeling applied and Mean Overlay on the wafer. The second main topic will be dedicated on the faster cycle time validation. This universal design (figure1) shows optimum performances with accuracy package-options and multiple wavelengths approach on YS-S375. The Universal design performance will be compared to the reference target and validated with an on-product measurement methodology (Holistic Metrology Qualification, HMQ) to deliver an optimized and accurate recipe to the production line. The metrology target could be used straight away on non-critical layers. To fastener the on-product target design validation and bypassing reticles fabrication, the metrology targets will be printed with e-beam lithography tool.




Figure1: Universal design including metrology targets with pitches varying from 600 nm (reference) to 2000 nm and size varying from $16 \times 16 \mu\text{m}^2$ to $30 \times 30 \mu\text{m}^2$

REFERENCES

- [1] Achieving Optimum Diffraction Based Overlay Performance, Philippe Leray, Proc. SPIE. 7638, Metrology, Inspection, and Process Control for Microlithography XXIV, 76382B. (2010)
- [2] On-product overlay enhancement using advanced litho-cluster control based on integrated metrology, ultra-small DBO targets and novel corrections. Kaustuve Bhattacharyya, Proc. SPIE. 8681, Metrology, Inspection, and Process Control for Microlithography XXVII, 868104. (2013)
- [3] Holistic approach using accuracy of diffraction-based integrated metrology to improve on-product performance, reduce cycle time, and cost at litho, Kaustuve Bhattacharyya, Proc. SPIE. 9424, Metrology, Inspection, and Process Control for Microlithography XXIX, 94241E. (March 19, 2015)
- [4] Bischo, J., Brunner, R., Bauer, J. J., and Haak, "Light diffraction-based overlay measurement, "Proc.SPIE 4344, (2001).
- [5] Bhattacharyya, K., Wright, N., van der Schaar, M., den Boef, A. J., Hinnen, P. C., Shahrjerdy, M., Wang, V., Lin, S., Wang, C., Ke, C.-M., Huang, J., and Wang, W. Y. H., New approaches for scatterometry based metrology for critical distance and overlay measurement and process control," Journal of Micro/Nanolithography, MEMS, and MOEMS 10, (2011).
- [6] Blancquaert, Y., Dezaudier, C., Depre, J., Miqyass, M., and Beltman, J. Performance of ASML Yield-Star DBO overlay targets for advanced lithography nodes C028 and C014 overlay process control," Proc.SPIE 8681, (2013).
- [7] Smilde, H.-J. H., den Boef, A., Kubis, M., Jak, M., van Schijndel, M., Fuchs, A., van der Schaar, M., Meyer, S., Morgan, S., Wu, J., Tsai, V., Wang, C., Bhattacharyya, K., Chen, K.-H., Huang, G.-T., Ke, C.-M., and Huang, Evaluation of a novel ultra small target technology supporting on-product overlay measurements," Proc.SPIE 8324, (2012).
- [8] Dettoni, F., Bouyssou, R., Dezaudier, C., Depre, J., Meyer, S., and Prentice, Enhanced 28 nm FD-SOI diffraction based overlay metrology based on holistic metrology qualification," Proc.SPIE 10145, 10145 (2017).
- [9] Smilde, H.-J. H., van Haren, R. J. F., van Buel, W., Driessens, L. H. D., Depre, J., Beltman, J., Dettoni, F., Ducote, J., Dezaudier, C., and Blancquaert, YS Target design optimization for overlay scatterometry to improve on-product overlay," Proc.SPIE 9424, (2015).
- [10] Smilde, H.-J. H., Martin Jak, A. d. B., van Schijndel, M., Bozkurt, M., Fuchs, A., van der Schaar, M., Meyer, S., Morgan, S., Bhattacharyya, K., Huang, G.-T., Ke, C.-M., and Chen, K.-H., Sub-nanometer in-die overlay metrology: measurement and simulation at the edge of finiteness," Proc.SPIE 8788, (2013).
- [11] Victor Calado, Jérôme Dépré, Clément Massacrier, Sergey Tarabrin, Richard van Haren, Florent Dettoni, Régis Bouyssou, and Christophe Dezaudier "Study of μ DBO overlay target size reduction for application broadening", Proc. SPIE 10585, Metrology, Inspection, and Process Control for Microlithography XXXII, 1058507 (13 March 2018);
- [12] Michael May, Blandine Minghetti, Jérôme Dépré, Pui Lam^c, Céline Lapeyre, Joungchel Lee " Stitched overlay evaluation and improvement for large field applications Proc. SPIE 2020

* e-mail : yoann.blancquaert@cea.fr

Keywords: Metrology, μ DBO, D4C, Scatterometry, process control, HMQ, Multi-Layer targets (MLT), multi-wavelength benefits, Universal designs