



HAL
open science

Microstructural investigation of (U,Pu)O_{2-x} with the Pu content and O/M ratio by Raman spectroscopy and imaging

Laetitia Medyk, Elodie Pascal, Philippe Martin, Gilles Montagnac, Patrick Simon

► To cite this version:

Laetitia Medyk, Elodie Pascal, Philippe Martin, Gilles Montagnac, Patrick Simon. Microstructural investigation of (U,Pu)O_{2-x} with the Pu content and O/M ratio by Raman spectroscopy and imaging. NuFuel 2019, Nov 2019, Villigen, Switzerland. cea-04741007

HAL Id: cea-04741007

<https://cea.hal.science/cea-04741007v1>

Submitted on 17 Oct 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Microstructural investigation of (U,Pu)O_{2-x} with the Pu content and O/M ratio by Raman spectroscopy and imaging

Medyk Laetitia^a, Philippe Martin^a, Elodie Pascal^a, Patrick Simon^b, Montagnac Gilles^c

^a CEA Marcoule/DEN/DMRC/SFMA/LCC – BP17171 30207 Bagnols-sur-Cèze, France

^b Conditions Extrêmes et Matériaux : Haute Température et Irradiation (CEMHTI) – CNRS, 45071 Orléans, France

^c Laboratoire de Géologie de Lyon, CNRS, ENS de Lyon, 69364 Lyon, France

The best candidate for the nuclear Sodium-cooled Fast Reactor fuel is the uranium-plutonium mixed dioxide (U,Pu)O_{2-x}. The plutonium content is planned to range between 19% to 40% mol. The fuel has to match various physico-chemical specifications: to be chemically homogeneous, oxygen hypostoichiometric (Oxygen/Metal ratio, with M=(U+Pu), between 1.94 and 2.00)... However, for a Pu content higher than 20%, and an O/M ratio lower than 1.98, at room temperature, the phase diagram of U-Pu-O system exhibits a miscibility gap domain [1]. The sample has then two phases of same structure but different O/M ratios. The demixtion of these two phases triggers the creation of cracks into the material. This phenomenon has to be avoided in order to keep a homogeneous microstructure. The behavior of the microstructure has then to be fully investigated.

Recently Talip *et al* [2] and Elorrieta *et al* [3] evidenced that Raman spectroscopy is a promising tool for characterizing (U,Pu)O₂ materials. Coupled with a microscope, this technique can be used to determine several physico-chemical properties at the grain scale. For instance, the cation distribution homogeneity, the grain size, and the crystal defects can be studied.

UO₂, PuO₂ and (U,Pu)O₂ all have the same Fm-3m structure. As the Raman active modes are determined by the symmetry, all these materials have similar Raman spectra. The main band is the T_{2g}, which corresponds to the asymmetrical stretching of the O-O bonds. The position of this band gives information on the chemical composition: O/M ratio, Pu content... Moreover, by studying sintered UO₂ samples by Raman cartographies, Maslova *et al* [4] have evidenced that the T_{2g} intensity is related to the grain orientation. By drawing the T_{2g} intensity map, the grains has been then revealed.

In the present work, this technique has been extended to (U,Pu)O_{2,00} samples. Like in the literature [4], the sample microstructure has been exhibited by performing T_{2g} intensity mapping. Furthermore, the variation in the T_{2g} position, related to the Pu content, has been studied and some heterogeneities in the Pu content were observed at the micrometric scale with the T_{2g} position map.

As this characterization tool was first developed for samples with O/M = 2.00, this method can be now extended to oxygen hypostoichiometric samples. The O/M ratio is fixed by heating the sample under reducing atmosphere (Ar/H₂ 5%). A dedicated device has been specifically designed for *in situ* Raman measurements [5]. The variation in the microstructure according both the Pu content and the O/M ratio values will be then studied.

[1] Sari *et al.* *J. Nucl. Materials*, 35, 267-77 1970

[2] Z. Talip *et al.* *J. Raman Spectrosc.*, 48 (5) 765–772, 2017

[3] J. M. Elorrieta *et al.*, *J. Nucl. Mater.*, 495, 484–491, 2017.

[4] O. A. Maslova *et al.*, *Mater. Charact.*, 129, 260–269, 2017.

[5] G. Montagnac *et al.*, *Carbon*, 54, 68–75, 2013