



Integrated design strategy for EU-DEMO first wall protection from plasma transients Fusion Engineering and Design 177 (2022) 113067

Francesco Maviglia, Christian Bachmann, Gianfranco Federici, Thomas Franke, Mattia Siccini, Raffaele Albanese, Roberto Ambrosino, Wayne Arter, Roberto Bonifetto, Giuseppe Calabro, et al.

► To cite this version:

Francesco Maviglia, Christian Bachmann, Gianfranco Federici, Thomas Franke, Mattia Siccini, et al.. Integrated design strategy for EU-DEMO first wall protection from plasma transients Fusion Engineering and Design 177 (2022) 113067. *Fusion Engineering and Design*, 2022, 178, pp.113125. 10.1016/j.fusengdes.2022.113125 . cea-04765260

HAL Id: cea-04765260

<https://cea.hal.science/cea-04765260v1>



Submitted on 5 Nov 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License



Integrated design strategy for EU-DEMO first wall protection from plasma transients Fusion Engineering and Design 177 (2022) 113067



Francesco Maviglia ^{a,b,*}, Christian Bachmann ^{a,n}, Gianfranco Federici ^a, Thomas Franke ^{a,c}, Mattia Siccino ^{a,c}, Raffaele Albanese ^d, Roberto Ambrosino ^d, Wayne Arter ^m, Roberto Bonifetto ^e, Giuseppe Calabro ^f, Riccardo De Luca ^f, Luigi E. Di Grazia ^o, Emiliano Fable ^c, Pierluigi Fanelli ^f, Alessandra Fanni ^g, Mehdi Firdaouss ^h, Jonathan Gerardin ⁱ, Riccardo Lombroni ^f, Massimiliano Mattei ^d, Matteo Moscheni ^e, William Morris ^m, Gabriella Pautasso ^c, Sergey Pestchanyi ^l, Giuseppe Ramogida ^b, Maria Lorena Richiusa ^m, Giuliana Sias ^g, Fabio Subba ^e, Fabio Villone ^d, Jeong-Ha You ^c, Zsolt Vizvary ^m

^a EUROfusion – Programme Management Unit, Boltzmannstrasse 2, 85748 Garching, Germany

^b Associazione EURATOM-ENEA sulla Fusione, C.R. Frascati, C.P. 65-00044 Frascati, Rome, Italy

^c Max-Planck-Institut für Plasmaphysik, Garching, Germany

^d Consorzio CREATE, Univ. Napoli Federico II - DIETI, 80125 Napoli, Italy

^e NEMO Group, Dip. Energia, Politecnico di Torino, C.so Duca degli Abruzzi24, Torino 10129, Italy

^f DEM Department, University of Tuscia, Largo dell'Università, 01100 Viterbo, Italy

^g Electrical and Electronic Engin. Dept.-University of Cagliari, Piazza D'Armi, 09123, Cagliari, Italy

^h CEA, F-13108 St Paul-Lez-Durance, France

ⁱ Institute of Plasma Physics, Czech Academy of Sciences, Prague, Czech Republic

^l KIT, Hermann-von-Helmholtz-Platz 1, Eggenstein-Leopoldshafen, Germany

^m CCFE, Culham Science Centre, Abingdon, Oxon, OX14 3DB, UK

ⁿ Technical University of Denmark, Lyngby, Denmark

^o Consorzio CREATE, Univ. della Campania L. Vanvitelli, Dip. Ingegneria, 80131 Aversa, Italy

The publisher regrets that [Table 1](#) has the wrong formatting. The correct version of the table is hereafter reported:

DOI of original article: <https://doi.org/10.1016/j.fusengdes.2022.113067>.

* Corresponding author.

E-mail address: francesco.maviglia@euro-fusion.org (F. Maviglia).

Table 1

Summary of all the plasma steady state and transient cases analyzed. The results, in the Output columns, show the HF due to charged particles (in MW/m², while in **bold** are indicated in GW/m²), evaluated with 3D field-line tracing codes (except the mitigated disruption where, instead, the photonic radiation, including toroidal and poloidal peaking factors, is reported). For the SOF and EOF are indicated in brackets, in *italic*, the HF including the radiation. *represents a D-VDE with the plasma shifted downwards (conservative). A subset of critical cases, in the output columns, is indicated with a superscript number within brackets

Inputs					Outputs: max HF (MW/m ²) <i>(Italic)</i> : with radiation, Bold : GW/m ²				
Scenario	Case	P _{SOL} (MW) +(P _{RAD})	λ _q (mm)	Deposition time	OML	UL	OLL	IML	FW
<u>SOF</u>	Diverted	69 +(300 core + 130 SOL)	50	Steady state	0.53 (0.65)	0.82 (1.10)	0.09 (0.33)	0 (0.19)	0.40 (0.59)
<u>EOF</u>	Diverted	69 +(300 core + 130 SOL)	50	Steady state	0.54 (0.74)	1.25 (1.42)	0.1 (0.36)	0.9 (1.11)	0.48 (0.67)
Min disr	Diverted	69	50	15-50ms	<0.01	0.13	0.01	3.06	0.69
ELM	Diverted	69	50	15-50ms	1.40	0.56	0	0	1.48
<u>Ramp-Up</u>	Limited	3.5	6	17.5-35s	2.37	0	0	0	0.29
<u>Ramp-Down</u>	Limited	5	6	25-50s	<0.01	<0.01	<0.01	0.02	0.01
		5	50	25-50s	<0.01	<0.01	<0.01	1.39	0.60
U-VDE	<u>First touch</u>	69	1	20-35ms	<0.01	114 ⁽²⁾	<0.01	0	0
		69	5	20-35ms	<0.01	15.6	<0.01	0	0.02
	<u>TQ</u>	325·10 ³	7	1-4ms	<0.01	63 ⁽³⁾	0	<0.01	138 ⁽⁸⁾
	<u>Current Quench</u>	10	10	74-200ms	<0.01	2.52	0	<0.01	0.01
		10	30	74-200ms	<0.01	1.53	0	<0.01	0.11
D-VDE	<u>First touch</u>	10 (*69)	10 (*1)	15-35ms	<0.01 (*0.01)	0 (*0)	<0.01 (*24.8)	<0.01 (*<0.01)	<0.01 (*<0.01)
		10 (*69)	30 (*5)	15-35ms	<0.01 (*0.01)	0 (*0)	<0.01 (*7.83)	<0.01 (*<0.01)	0.08 (*0.01)
	<u>TQ</u>	325·10 ³	7	1-4ms	0.77 (*182) ⁽¹⁾	0 (*0)	4.4 (*306) ⁽⁴⁾	0.84 (*11.3)	8.11 (*292) ⁽⁹⁾
	<u>Current quench</u>	10	10	74-200ms	<0.01	<0.01	<0.01	<0.01	<0.01
		10	30	74-200ms	<0.01	<0.01	<0.01	<0.01	<0.01
H-L transition	<u>Limited (inboard)</u>	30	2	1-5s	<0.01	<0.01	<0.01	64 ⁽⁵⁾	1.06
		30	4	1-5s	<0.01	<0.01	<0.01	44.5 ⁽⁶⁾	5.48
Major Disruption (MD)	<u>TQ</u>	325·10 ³	7	1-4ms	0.61	1.46	0.84	1.44 ⁽⁷⁾	333 ⁽¹⁰⁾
	<u>CQ</u>	10	10	74-200ms	<0.01	<0.01	<0.01	0.01	<0.01
		10	30	74-200ms	<0.01	<0.01	<0.01	0.21	0.05
Mitig.disr.	TQ	P _{RAD} : 2.2 GW			1ms	2 ⁽¹¹⁾	1.8 ⁽¹¹⁾	1.8	1.5
								2 ⁽¹¹⁾	

The publisher would like to apologise for any inconvenience caused.