



Study of In_{0,53}Ga_{0,47}As/ InP/InAlAs/InP heterostructures by TOF-SIMS and HAXPES

Guy-Vano Tsamo Tagougue, Eugénie Martinez, Marc Veillerot, Vincent Thoreton, Thierry Baron, Franck Bassani, Mickael Martin

► To cite this version:

Guy-Vano Tsamo Tagougue, Eugénie Martinez, Marc Veillerot, Vincent Thoreton, Thierry Baron, et al.. Study of In_{0,53}Ga_{0,47}As/ InP/InAlAs/InP heterostructures by TOF-SIMS and HAXPES. SIMS 24, Jun 2024, Rochelle, France. cea-04862165

HAL Id: cea-04862165

<https://cea.hal.science/cea-04862165v1>

Submitted on 2 Jan 2025

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Study of $\text{In}_{0.53}\text{Ga}_{0.47}\text{As}/\text{InP}/\text{InAlAs}/\text{InP}$ heterostructures by TOF-SIMS and HAXPES

G.Tsamo^{a,b*}, E. Martinez^a, M. Veillerot^a, V.Thoréton^a, F.Bassani^b, M.Martin^b, T. Baron^b

^a Univ. Grenoble Alpes, CEA, Leti, F-38000 Grenoble, France

^b Univ. Grenoble Alpes, CNRS, CEA/LETI Minatec, Grenoble INP, LTM, 38000 Grenoble, France

*Contact: guy-vano.tsamotagougue@cea.fr

Abstract

The advantages of III-V semiconductors such as their direct gap and high charge carrier mobility make them interesting for optoelectronics applications, high-frequency transistors (HBTs) and high electron mobility transistors (HEMTs) [1]. Although the growth of heterostructures such as $\text{In}_{0.53}\text{Ga}_{0.47}\text{As}$ on InP has a tuned lattice parameter, interdiffusion of the main elements and dopants can reduce device performance. Time-of-flight secondary ion mass spectrometry (TOF-SIMS) has proved ideal for studying buried interfaces [2]. For III-V semiconductors, the choice of abrasion gun and analyzer polarity is a key factor in achieving good ionization efficiency of the elements to be monitored [3]. For such materials, for example, it has been shown that using a dioxygen gun (O_2^+) for sputtering results in depth resolution degradation due to the formation of an oxide layer at the bottom of the crater [4].

In this presentation, we'll show how the use of two analyzer polarities and the choice of abrasion and analysis guns (Cs^+ and Bi_3^+) enable complete monitoring of the main elements, dopants and impurities in heterostructures such as $\text{In}_{0.53}\text{Ga}_{0.47}\text{As}/\text{InP}/\text{InAlAs}/\text{InP}$. We'll compare TOF-SIMS analyses using Cs^+ and O_2^+ sputtering sources. From AFM images of the crater formed, we obtain roughness values around 2 and 6 nm using the Cs^+ and O_2^+ sources respectively. This difference is due to the formation of an oxide layer at the bottom of the crater in the case of the O_2^+ source, which destroys depth resolution. High-energy photoelectron spectroscopy (HAXPES) with a chromium source $\text{Cr K}\alpha$ ($h\nu=5415$ eV) [5] will be used to quantify the elemental composition and investigate chemical environments at the buried InGaAs/InP interface, showing for instance the absence of interfacial oxidation.




Figure 1: TOF-SIMS profiles and AFM images of the crater formed for Cs^+ and O_2^+ abrasion respectively for $\text{In}_{0.53}\text{Ga}_{0.47}\text{As}/\text{InP}/\text{InAlAs}/\text{InP}$ heterostructures.

- [1] J. W. Lambrechts *et al.*, *IEEE Access*, vol. 12, no. January, pp. 21402–21419, 2024.
- [2] T. Spelta *et al.*, *Solid. State. Electron.*, vol. 208, no. August, pp. 2–4, 2023.
- [3] B. Gong and C. E. Marjo, *Surf. Interface Anal.*, vol. 48, no. 7, pp. 422–427, 2016.
- [4] M. Kachan *et al.*, *Appl. Surf. Sci.*, vol. 231–232, pp. 684–687, 2004.
- [5] O. Renault *et al.*, *Faraday Discuss.*, vol. 236, pp. 288–310, 2022.

Acknowledgements

This work, carried out (in part) on the Plate-Forme de Nano-Caractérisation (PFNC), benefited from government funding managed by the Agence Nationale de la Recherche under the "Recherche Technologique de Base" and France 2030 programs (ANR-22-PEEL-0014). We would also like to thank Labex Minos for funding this project.